

Flat Top TowerCrane 6tons QTZ63-PT5510 55m Boom Long Tower Kren Chart

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

 Application: 	Buildings And Projects
• Туре:	Fixed With Tower Head
• Max. Load:	6t
 Jib Length: 	55m
• Tip. Load:	1.0t
 Power supply: 	380V/50Hz Or According To Client's Requirements
 Mast section: 	1.6*1.6*2.5m (Block Type)
Main Chord:	135*10mm (square Tube)

China

1

LC

TT, LC

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

\$60600-65900 per set

30 sets per month

containers.

QTZ63(PT5510) Tower Crane

Naked packing, 5*40'HQ+1*20'GP

15 days after receiving the deposit or origin



More Images





Flat Top TowerCrane 6tons QTZ63-PT5510 55m Boom Long Tower Kren Chart

Technical Parameters

Nominal Lifting Moment: 630 KN.m
 Working Range: 3-55 m
 Max. Lifting Capacity: 6 t
 Independent Standing Height: 40 m
 Attached Standard Height: 150 m
 Lifting Speed: 80/40/8.5 40/20/4.25 m/mim
 Slewing Speed: 0.6 r/min

Specification

Rated lifting	moment (kN.m)	630				
Lifting height (m)		Rope fall	Free-standing stationary crane		Anchored crane	
		α2	40		150	
		α4	40		150	
Working radius (m)		Max. working radius		55		
		Min. workir	Min. working radius 3		3	
Max. lifting capacity (t)		5				
Hoisting mechanism	Rope fall	α2		α4		
	Speed (m/min)	80/40/8.5		40/20/4.25		
	Lifting weight (t)	1	2.5	2.5	5	
	Power (kW)	24/24/5.5				
Tolleying mechanism		Speed (m/min)		0.6		
		Power (kW)		3.7		
Slewing mechanism		Speed (r/min)		0.4		
		Power (kW)		4		

Advantage

1. 15 years of experience in supplying new Topless tower crane with HYCM Brand which export to more than 20 countries with CE / ISO Certificates.

- 2. Stationary / Traveling and internal climbing type topless tower crane are available.
- 3. Quality Control: Impeller blasting/rust protection paint, advanced painting process and Strict and experience welding line
- 4. New designed mast, can be used to Internal and external climbing tower crane
- 5. Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
- 6. Engineers available to service machinery overseas.
- 7. For warranty: 12 months from the B/L date.

Why choose us

- 1. A professional tower crane supplier in China with 15 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

Applications

It's used in construction building site, such as Multi commercial housing, High rise building, Skyscraper, and Workshop Material handling etc.

Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com

by hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China