DC1830 Small Derrick Crane 4 Ton Capacity at 100m Height 18m Luffing

Basic Information

Place of Origin: China

Brand Name: GUHENG AVITT or others
Certification: CE, ISO, GOST, CU-TR
Model Number: QD80(1840) Derrick Crane

• Minimum Order Quantity: 1 set

• Price: \$28800-43600 per set

Packaging Details: Naked packing, 1*20'GP containers per set

DC1830 Derrick Crane

• Delivery Time: 30 days after receiving the deposit or origin

LC

• Payment Terms: Western Union, L/C, T/T

Supply Ability: 40 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 4tJib Length: 18mTip. Load: 3t

• Power supply: 380V/50Hz Or According To Client's

Requirements

Color: Yellow Or According To Clients Need

• Highlight: 8 ton luffing jib derrick crane,

18m boom long jib crane, HYCM derrick crane with warranty

Product Description

DC1830 Small Derrick Crane 4 Ton Capacity at 100m Height 18m Luffing Jib

Introduction of DC1830 Derrick Crane

- 1. The Derrick cranes is fixed to the roof.
- 2. The base is then attached to the slewing unit that allows the crane to sewing.
- 3. On top of the slewing unit there are two main parts which are: the long jib, shorter counter-jib,
- 4. The long jib is the part of the crane that carries the load.
- 5. The crane operator either sits in a cab at the top of the tower or controls the crane by radio remote control from the ground.
- 6. The lifting hook is operated by the crane operator using electric motors to manipulate wire rope cables through a system of sheaves.

Specification of DC1830 Derrick Crane

Model		DC1830 Derrick Crane
Working Radius (m)		18
Max. Load Capacity (T)		4
Tip Load (T)		3
Height (m)		200
Hoisting Mechanism	Speed (m/min)	0-8 0-26
	Motor power (kw)	7.5
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	4
Trolleying Mechanism	Speed (m/min)	2
	Motor power (kw)	11
Total Power (kw)		22.5
Power Supply		380V/50Hz, 380V/60Hz or according to clients needs

Feature of DC1830 Derrick Crane

- (1) Reasonable structure for less costing and maintenance.
- (2) Favorable performance to improve your working capacity.
- (3) Smooth starting and stopping to improve you security sense.
- (4) Low noise, commodious cabin and good view can make you happiness operating and accurate operating.
- (5) Credible electric parts to guarantee the crane safety in operating.

Safety device of DC1830 Derrick Crane

- (1) Weight overload protection device
- (2) Lifting height limit device
- (3) Voltage lower protection function
- (4) Phase sequence protection function
- (5) Emergency stop function

Why choose us

- 1. A professional tower crane supplier in China with 30 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

Photos of DC1830 Derrick Crane





0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China