


DC2135 5t Load Derrick Crane Luffing Jib Dismantle Inner Climbing Tower Crane

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GUHENG AVITT or others
- Certification: CE, ISO, GOST, CU-TR
- Model Number: DC2135 Derrick Crane
- Minimum Order Quantity: 1 set
- Price: \$43600-52900 per set
- Packaging Details: Naked packing, 1*40'HQ containers per set DC2135 Derrick Crane
- Delivery Time: 30 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 5t
- Jib Length: 21m
- Tip. Load: 3.5t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Color: Yellow Or According To Clients Need
- Highlight: 18m jib luffing derrick crane,
full VFD control derrick crane,
10TONS QD1840 HYCM crane

for more products please visit us on hycmtowercrane.com

Product Description

DC2135 5t Load Derrick Crane Luffing Jib Dismantle Inner Climbing Tower Crane

Feature of DC2135 Derrick Crane

- (1) Special design of separate-settled. Low center weight of gravity in slewing, large lifting capacity and reasonable mechanism design.
- (2) Big luffing range. The slewing radius can reach 21 m. More efficiency will come true by changing luffing range under rated load.
- (3) Three mechanisms-lifting, luffing and slewing, with satisfied performance in shifting and high efficiency, are operated easily.
- (4) With kinds of safety facilities, as limiter for lifting moment, slewing limiter and luffing limiter. Once over load happen, the facilities will turn down power automatically right away.
Also, an electronic transducer for load is fixed to cut down power when overloading appears.
- (5) Installation and disassembly is convenient. The product can be transferred to other site in short time and maintenance is very easy and convenient. All spare parts satisfy relative standards.
- (6) Electric control box is equipped to the crane which is operated easily and safely.

Specification of QD80 Derrick Crane

Model		DC2135 Derrick Crane
Working Radius (m)		21
Max. Load Capacity (T)		5
Tip Load (T)		3.5
Height (m)		200
Hoisting Mechanism	Speed (m/min)	0-9 0-30
	Motor power (kw)	11
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	4
Trolleying Mechanism	Speed (m/min)	2.1
	Motor power (kw)	11
Total Power (kw)		26
Power Supply		380V/50Hz, 380V/60Hz or according to clients needs

Control method of DC2135 Derrick Crane

- (1) Pendant line control
- (2) Remote control
- (3) Cabin control
- (4) Choose any two together

Painting of DC2135 Derrick Crane

- (1) Process: Sandblast, Primer, finishing paint
- (2) Color: Yellow, Red, Blue etc. (according to your demand).

Application of DC2135 Derrick Crane

1. Shipping platforms
2. High-rise buildings
3. Construction sites

Why choose us

1. A professional tower crane supplier in China with 30 years experience
2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
3. Hydraulic self-climbing mechanism
4. Variable-frequency slewing mechanism
5. Variable-speed frequency PLC control System
6. Operation data display screen and Safety monitoring system (Black Box)
7. Various safety devices

Photos of DC2135 Derrick Crane



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China