

TC7040 16TONS Remote Control Real Estate The Tower Crane Cat Head Type

Basic Information

• Place of Origin: China

Brand Name: HYCM TOWER CRANE
Certification: CE, ISO, GOST, CU-TR
Model Number: QTZ315(7040) Tower Crane

Minimum Order Quantity:

• Price: \$168300-184500 per set

Packaging Details: Naked packing, 9*40'HQ containers.

• Delivery Time: 40 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

Supply Ability: 2 sets per month



Product Specification

Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 16 T
Jib Length: 70 M
Tip. Load: 4.0 T

• Mast section: 2*2*3 M Potain Type

Electric Box: Schneider

• Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

Color: Yellow, Red Or According To Clients Needs



More Images



Product Description

TC7040 16TONS Remote Control Real Estate The Tower Crane Cat Head Type

Short Parameters

1.QTZ315(TC7040) Topkit Tower Crane

2. Type: fixed and external climbing

3. jib length: 70m4. tip load:4.0t5. max.laod:16t

6.freestanding height:50m

Introduction

- 1) We are a professional manufacture of construction machine, have CE certification, with high quality and competitive price 2) Tower crane is a combination of advanced technologies from home and abroad, it is equipped with a hydraulic self-raising mechanism and frequency-converting slewing mechanism.
- 3) The crane has a complete set of safety devices, which can guarantee the safety and high efficient operation of the equipment, It is equipped with height limiter, moment limiter, radius-changing limiter and weight limiter, etc.
- 4) Our products have been exported to many countries and areas in Europe, America, Australia, the Middle East and Southeast Asia etc.

Specification

Specification		
Model		TC7040 Tower Crane
Туре		Fixed with outside climbing of buildings
Working Radius (m)		70
Max. Load Capacity (T)		16
Tip Load (T)		4.0
Free standing height (m)		48
Max. Height with anchorages (m)		180
Mast Section dimension (m)		2×2×3,
		Angle steel 200×26mm
Hoisting Mechanism Speed (m/min)		0-60 0-30
	Motor power (kw)	45
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	2*5.5
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		61.5
Power Supply		380V/50Hz, 220V/60Hz or others

Features

Durable, safe and low-maintenance cranes live up to the highest manufacturing standards. They are durable, operator-friendly, safe and have low maintenance requirements.

Quality materials for durability

Our components are traceable back to original premium-quality manufacturers, ensuring that they can easily be replaced when necessary. The quality of our components assure good resistance to fractures under conditions of high loading and low temperatures.

Quality steel mill-certified to European EN standards.

High-quality components from suppliers represented worldwide.

Protected: For safeguarding, all components are fitted into housing of the highest quality. Fully enclosed motors - IP55 - ensure long lasting motor insulation.

Easily identifiable: Cables and components are numbered or marked for easy identification, reducing maintenance time and costs.

Efficient: Virtually all internal electrical installation is done using multi-plug connections which reduces erection time.

Safety devices:

- 1): Hoist height limit
- 2): Over speed limit
- 3): Over load limit
- 4): Lifting moment limit
- 5): Slewing angle limit
- 6): Emergency stop button
- 7): Obstruction light (tip of jib, tower head)
- 8): Wind lock device.

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408





hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China