



1TONS SS100 Material Elevator Building Hoist 24m to 60m Height 380V 60Hz

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC Building Hoist
- Minimum Order Quantity: 1 set
- Price: \$8850-10200 per set
- Packaging Details: Naked packing, 1*40'HQ containers.
- Delivery Time: 15 days after receiving the deposit
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Wire Rope Climbing
- Max. Load: 1tons
- Max. Height: 60m
- Rated Speed: 22m/min
- Power supply: 380V 60Hz Or According To Client's Requirements
- Motor Power: 5.5kw
- Model: Ss100
- Mast Section Size: 800*800*1508mm



More Images



Product Description

1TONS SS100 Material Elevator Building Hoist 24m to 60m Height 380V 60Hz

Introduction

SS100 Material Elevator is a product introduced in accordance with GB/T10054-2005 "Construction Elevator" research and development, widely used in the vertical transport of high-rise and multi-storey construction, mining, workshop materials. The utility model has the advantages of simple structure, quick and easy installation and disassemble, safe and reliable use, economic benefits and high work efficiency.

Specification

No.	Item	Unit	Value
1	Height	Freestanding	m
	Max. height	m	24
2	Mast section size	m×m×m	0.8×0.8×1.508
3	Cage size	m×m×m	3×1.3×1.9
4	Rated load	kg	1000
5	Rated speed	m/min	22
6	Motor	Y132M-4-5.5KW	
7	Brake	MZD-- 200	
8	Wire rope	6*19-11-1750-1	
9	Working condition	-20 +40	

Distinctive Features

1. Safety protection device is complete and reliable. For safety device with national patent technology, make the machine working reliability among the top of the same products.
 2. Modular design, through different collocation, different speed, different lifting weight can be combined from the elevator specifications. The product standard, practicability and generalization are greatly improved.
 3. Smooth operation and comfort. Because the machine will be top drive unit in the cage, cage net space increases; At the same time also make driving more smoothly, mechanical vibration, brings to the operation staff a comfortable and spacious environment.
- Use this machine is a wise choice, you set the construction lifter can become your modernization construction's right-hand man, for your construction efficiency.

Safety device

1. Overweight protection
2. Phase sequence protection
3. Safety door protection
4. Interlayer protection
5. Motor reverse protection
6. Mechanical anti-roll top protection
7. Sensor failure protection
8. Motor short circuit or overload protection
9. Bell output function
10. Data protection

Picture





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China