

ZLP 630 Climbing Platform High Window Cleaning Equipment 440V 60Hz Philippines

Basic Information

• Place of Origin: China

• Brand Name: HYCM or others

Certification: ISO,CE

Model Number: ZLP630 Platform

• Minimum Order Quantity: 1 set

• Price: \$2170-2490 per set

• Packaging Details: LCL or 20'GP, 40'HQ construction

• Delivery Time: 7-10 days

Payment Terms: Western Union, L/C, T/T

• Supply Ability: 50 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And Projects

• Type: High Window Cleaning Equipment

Rated Load: 630kg
Working Height: 100m
Rated Speed: 9-11 M/min
Power supply: 440V 60Hz
Motor Power: 2*1.5 Kw

Platform Material: Steel, Hot Galvanized Or Aluminum

Model: ZLP 630



More Images



Product Description

ZLP 630 Climbing Platform High Window Cleaning Equipment 440V 60Hz Philippines

Description

ZLP series Swing Stage, which is developed and produced by HYCM is ideal for building facade construction, decoration, cleaning and maintenance. It is also widely used in elevator installing, ship building and repairing, or in other areas such as big-size tank, bridge, embankment and chimney. ZLP series versatile knock-down platform provides workers safer, easier and more efficient platform access.

Absolutely guarantee life safety during Aerial working. Safety lock fasten the steel rope immediately once the suspended platform tilts or the steel rope slips out of the hoist; Electric control system is designed with leakage protection, over-heat protection, current overload protection and brake stop

Specification

Model No.		ZLP630
Rated load(kg)		630
Lifting speed(m/min)		9 11
Hoister model		LTD63
Motor power(kw)		2×1.5
Brake torque(N.m)		15.2
Rated stretch of front beam(mm)		1100-1700
Suspending Platform	No. of platform rack	Single rack
	No. of platform	3
	L×W×H(mm)	(1.5+2+2.5)×690×1180
Suspending mechanism(kg)		2×175 Kg
Counterweight(kg)optional		25×40pcs
Diameter of steel rope(mm)		8.3
Voltage(v) 3PHASES		220V/380V/415V (customized)
Ambient temperature		-20 ~+40
Ambient relative humidity		≤ 90%(25)

The main Part:

1. Suspension Mechanism and Counterweight

The Height of the platform can be adjusted within 1150-1750mm with arm which can be stretched out and drawn back, it can be widely used parapet and complicated building in different height, and we can also supply customized platform to meet different requirement from the customers

2. Working Platform

Different material for different requests: Steel, Hot galvanized and Aluminum.

Various platform length for clients to choose.

3. Hoist Motor

LTD6.3 "a" shape hoist

4. Electrical Control box

Installed with international and national famous brands electrical components, our electrical control system consists of many protection devices, Such safety devices as electrical leakage protection device, automatic limited switch, overheat protection, emergency brake, current coverload proof, which make operate more easier, safer and reliable.

5. Safety Lock

When the steel wire rope is broken, blocked, slip out of he hoist or the working platform inclines, the safety lock will lock the rope within 100mm, this safety device is high advanced in China now.

Why choose us

- 1. A professional tower crane supplier in China with 15 years experience
- 2. Exported to more than 20 countries with ISO9001 Certifications
- 3. Varialbe-speed frequency PLC control System
- 4. Operation data display screen and Safety monitoring system (Black Box)
- 5. Various safety devices





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China