



## ZLP800 Building Gondola Construction Suspended Platforms 380v 60Hz Power

Our Product Introduction

for more products please visit us on hycmtowercrane.com

### Basic Information

- Place of Origin: China
- Brand Name: HYCM or others
- Certification: ISO, CE
- Model Number: ZLP800 Platform
- Minimum Order Quantity: 1 set
- Price: \$2340-2590 per set
- Packaging Details: LCL or 20'GP, 40'HQ construction
- Delivery Time: 7-10 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 50 sets per month



### Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Building Gondola
- Load: 800kg
- Standard Height: 100 M
- Rated Speed: 9-11 M/min
- Power: 380v 60Hz
- Motor Power: 2\*1.8 Kw
- Platform Material: Hot Galvanized And Aluminum
- Platform Length: 6m Or 7.5m
- Model: ZLP800



### More Images



## Product Description

### ZLP800 Building Gondola Construction Suspended Platforms 380v 60Hz Power

#### Short Parameter

1. ZLP800 Suspended Platform
2. rated load: 800kg
3. height: 100m
4. speed: 9-11m/min

#### Applications

1. Cleaning and maintaining of the exterior wall of high-rise building.
2. Painting, decoration and refurbishing of exterior walls.
3. Installation projects and other construction working of outer walls of high-rise building.
4. Aerial working of ship, large tower, bridge, dams and large chimneys.
5. Install and maintain for high-rise building elevator hoistway, shipbuilding industry, seagoing vessel, warships welding maintain.

#### Specification

|                                     |                                   |                   |
|-------------------------------------|-----------------------------------|-------------------|
| Model                               | ZLP800 Suspended Working Platform |                   |
| Rated load(kg)                      | 800                               |                   |
| Lifting speed(m/min)                | 8.2                               |                   |
| Motor power(kw)                     | 2×1.8 50HZ/60HZ                   |                   |
| Brake torque(Km)                    | 15.2                              |                   |
| Steel rope angle adjusting range(°) | 3°- 8°                            |                   |
| Distance between two steel rope(mm) | ≤100                              |                   |
| Rated stretch of front beam(mm)     | 1100-1700                         |                   |
| Suspending Platform                 | Locking                           | Aluminum alloy    |
|                                     | Nr. of platform rack              | Single rack       |
|                                     | Nr. of platform                   | 3                 |
|                                     | L×W×H(mm)                         | (2500×3)×690×1180 |
|                                     | Weight(kg)                        | 217               |
| Suspending mechanism(kg)            | 2×175 Kg                          |                   |
| Counterweight(kg) optional          | 25×40pcs                          |                   |
| Diameter of steel rope(mm)          | 8.6                               |                   |
| Voltage(v) 3PHASES                  | 220V/380V/415V (customized)       |                   |

#### Features

1. Our suspended working platform can be widely used parapet and complicated building in different height. And we can also supply customized platform to meet different requirements from customers.
2. Suspension power Working Platform is a temporary, flexible high access equipment for maintenance and construction work. distinguished from permanent access equipment. It can be disassembled conveniently.
3. It compared with traditional scaffolding, can save labours and time to maintain the high buildings, such as industry workshop, water tower, bridge, TV tower, big chimney, cenotaph, dam, etc.
4. Besides, Suspension Working Platform can be used to lift specific weight.
5. Suspension Working Platform is a good helper for construction and decoration of high buildings.
6. ZLP800 suspended platform uses LTD80 hoisting motor. It has electromagnetic brake motor, centrifugal speed limiting device, two steep speed reducer and "a" type rope winding system.
7. Hoisting motor can wind rope automatically. Operator only need to insert rope into the motor.

#### Pictures



emma1109@foxmail.com  
0086 18254159408

**More products available:**

**Tower Cranes**

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

**SC Construction Man and Material Elevator**

- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

**SS Building Material Lift / Hoist**

- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

**ZLP Suspended Platform**

- Most popular model ZLP630, ZLP800: 630KG AND 800KG



**Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane**



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China