



ZLP 800 Suspended Platform Aluminum Electric Scaffolding Load Passengers to Work

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or others
- Certification: ISO, CE
- Model Number: ZLP800 Platform
- Minimum Order Quantity: 1 set
- Price: \$2340-2590 per set
- Packaging Details: LCL or 20'GP, 40'HQ construction
- Delivery Time: 7-10 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 50 sets per month



Product Specification

- Condition: 100% New
- For: Load Passengers To Work
- Type: Electric Scaffolding
- Rated Load: 800kg
- Standard Height: 100 M
- Rated Speed: 9-11 M/min
- Power: 380v 60Hz
- Motor Power: 2*1.8 Kw
- Platform Material: Aluminum
- Platform Length: 6m Or 7.5m
- Model: ZLP 800



More Images



Product Description

ZLP 800 Suspended Platform Aluminum Electric Scaffolding Load Passengers to Work

Introduction:

1m, 2m, 3m, 1.5m, 2.5m to the length made.
 In any Combination Rated Load: 800KG
 Rated Lifting Speed: 8-11m/min
 Length of Platform: 6000mm or 7500mm
 Surface Proceeding: Steel materials(Galvanized,Spraying) or Aluminum
 Lifting Height: 100m
 Cable: 95m
 Max Lifting Height:200m
 Steel Rope: 8.3mm or 9.1mm
 Hoist Power: 1.8KW*2
 Voltage:380V, 50HZ, Three-Phase(standard), 440V/60HZ, 220V/60Hz or others.
 Safety Lock Permission Force of Impact: 30KN
 Locking Cable Angle: 3°~ 8°
 Suspension Mechanism Front Beam Overhang: 1.3 ~ 1.5m ±0.26
 Support Adjustable Height: 1.44 ~ 2.14m ±0.26
 Counter Weight: 1000KG or others
 Package: Wooden or Naked by Containers

Applications

1. Cleaning and maintaining of the exterior wall of high-rise building.
2. Painting, decoration and refurbishing of exterior walls.
3. Installation projects and other construction working of outer walls of high-rise building.
4. Aerial working of ship, large tower, bridge, dams and large chimneys.
5. Install and maintain for high-rise building elevator hoistway, shipbuilding industry, seagoing vessel, warships welding maintain.

Specification

Model	ZLP800 Suspended Working Platform	
Rated load(kg)	800	
Lifting speed(m/min)	8.2	
Motor power(kw)	2×1.8 50HZ/60HZ	
Brake torque(Km)	15.2	
Steel rope angle adjusting range(°)	3°- 8°	
Distance between two steel rope(mm)	≤100	
Rated stretch of front beam(mm)	1100-1700	
Suspended Platform	Locking	Aluminum alloy
	Nr. of platform rack	Single rack
	Nr. of platform	3
	L×W×H(mm)	(2500×3)×690×1180
	Weight(kg)	217
Suspending mechanism(kg)	2×175 Kg	
Counterweight(kg) optional	25×40pcs	
Diameter of steel rope(mm)	8.6	
Voltage(v) 3PHASES	220V/380V/415V (customized)	

Features

1. Our suspended working platform can be widely used parapet and complicated building in different height. And we can also supply customized platform to meet different requirements from customers.
2. Suspension power Working Platform is a temporary, flexible high access equipment for maintenance and construction work. distinguished from permanent access equipment. It can be disassembled conveniently.
3. It compared with traditional scaffolding, can save labours and time to maintain the high buildings, such as industry workshop, water tower, bridge, TV tower, big chimney, cenotaph, dam, etc.
4. Besides, Suspension Working Platform can be used to lift specific weight.
5. Suspension Working Platform is a good helper for construction and decoration of high buildings.
6. ZLP800 suspended platform uses LTD80 hoisting motor. It has electromagnetic brake motor, centrifugal speed limiting device, two steep speed reducer and "a" type rope winding system.
7. Hoisting motor can wind rope automatically. Operator only need to insert rope into the motor.



emma1109@foxmail.com
0086 18254159408





高空作业吊篮

高空作业吊篮主要用于高层建筑的外墙施工、装修、洗和保养，也可用于大型罐体，烟囱，水坝，桥梁，架的施工

Suspended working platform is an ideal equipment for facade construction, decoration, cleaning and maintenance, and is also widely used in elevator installation, shipyard, big tank, bridge, embankment and chimney.

- 设计新颖、安装简单、操作方便 •
- 结构紧凑、用料精良、使用寿命长 •
- 承载能力强、传动效率高、准确便捷 •
- 安全锁保护装置 •
- 电控系统安全保护装置 •
- 安全绳保护措施 •
- 保证安全运行 •

emma1109@foxmail.com
0086 18254159408

More products available:

Tower Cranes

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform

---Most popular model ZLP630, ZLP800: 630KG AND 800KG





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu
District, Jinan City, Shandong Province, China