

D5015 8T Luffing Tower Crane Full Invertor Control Box with 7.5m Base Mast

Basic Information

Place of Origin: ChinaBrand Name: HYCM

Certification: CE, ISO, GOST, CU-TR
 Model Number: D5015 Luffing Tower Crane

• Minimum Order Quantity: 1 set

• Price: \$107900-113500 per set

Packaging Details: Naked packing, 6*40'HQ containers.

• Delivery Time: 30 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 10 sets per month



Product Specification

Application: Buildings And ProjectsType: Fixed With Tower Head

Load: 8tLuffing Jib: 50mBase Mast: 7.5m

• Power supply: 380V/50Hz Or According To Client's

Requirements

Mast section: 1.6*1.6*3 M (split Type)
Main Chord: 180*18 Mm (angle Steel)



More Images





Product Description

D5015 8T Luffing Tower Crane Full Invertor Control Box with 7.5m Base Mast

Performance parameters

- Max. jib length: 50m;Max. lifting capacity 8t;
- Max. hoisting capacity at jib tip:1.5t;
- Rated lifting moment: 1200 Kn.m;
- Max. freestanding height: 27m; Max. working height of anchored crane: 160m

Specification

<u> </u>		
Model		QTD120 (5015) Luffing Tower Crane
Working Radius (m)		50
Max. Load Capacity (T)		8
Tip Load (T)		1.5
Free standing height (m)		37
Max. Height with anchorages (m)		160
Mast Section dimension (m)		1.6×1.6×3, angle steel 180×18mm
	Speed (m/min)	0-80 -040
Hoisting Mechanism	Motor power (kw)	24/24/5.4
	Speed (r/min)	0-0.6
Slewing Mechanism	Motor power (kw)	2*3.7
	Speed (m/min)	0-10
Trolleying Mechanism	Motor power (kw)	30
	Speed (m/min)	0.4
Jacking-up System	Motor power (kw)	7.5
Total Power (kw)		34
Power Supply		380V/50Hz or according to clients needs

Commercial Terms

Price: Negotiable

Delivery time: 30 days after receiving 30% advanced payment Trade terms: FOB (qingdao) Or CFR, CIF according to Clients needs

Terms of Payment: T/T or L/C (30% advanced payment, 70% before shipment)

Packing: Standard Exporting Packing Warranty: At least 12 months

Photos





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane





