

# QTZ315 Flat Top Tower Crane 75M Boom 3.2t Tip Load to UAE Market

## Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



## **Product Specification**

• Cor	ndition:	100% New
<ul> <li>App</li> </ul>	olication:	Buildings And Projects
• Тур	e:	Fix And External Climbing
<ul> <li>Loa</li> </ul>	ıd:	20t
• Boo	om:	75m
• Tip.	Load:	3.2t
• Mas	st section:	2*2*3m Potain Type
• Ele	ctric Box:	Schneider
<ul> <li>Pov</li> </ul>	ver Supply:	380V/50Hz, 415V/50Hz, 220V/50Hz According To Clients Need
• Cor	ntrol:	VFD Or Inverter

China

1

LC TT, LC

containers.

1 sets per month

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

\$189000-196800 per set

QTZ315 Flat Top Tower Crane

Naked packing, 12\*40'HQ+1\*40'OT

35 days after receiving the deposit or origin

Or



## More Images





## **Product Description**

#### QTZ315 Flat Top Tower Crane 75M Boom 3.2t Tip Load to UAE Market

#### Performance parameters

1.QTZ315(PT7532) Flat Top Tower Crane 2. Type: fixed and external climbing 3. jib length: 75m 4. tip load: 3.2t 5. max.laod: 20t

6.freestanding height: 50m

### Specification

opeenieuten				
Model		PT7532 Tower Crane		
Туре		Fixed with outside climbing of buildings		
Working Radius (m)		75		
Max. Load Capacity	(T)	20		
Tip Load (T)		3.2		
Free standing height	: (m)	50		
Max. Height with and	chorages (m)	180		
Mast Section dimens		2×2×3, Angle steel 200×26mm		
Hoisting Mechanism	Speed (m/min)	0-60 0-30		
	Motor power (kw)	45		
Slewing Mechanism	Speed (r/min)	0-0.6		
	Motor power (kw)	2*5.5		
Trolleying	Speed (m/min)	0-60		
Mechanism	Motor power (kw)	5.5		
Jacking-up System	Speed (m/min)	0.4		
	Motor power (kw)	5.5		
Total Power (kw)	•	61.5		
Power Supply		380V/50Hz, 380V/60Hz or others		

#### Why choose us

1. A professional tower crane supplier in China with 15 years experience

2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications

3. Hydraulic self-climbing mechanism

4. Variable-frequency slewing mechanism

5. Varialbe-speed frequency PLC control System

6. Operation data display screen and Safety monitoring system (Black Box)

7. Various safety devices

#### Features

1. This new design tower crane expands maximum jib length to 75 m and increases load charts over previous models offering the same lift capacity on the whole jib length, with a maximum load at the full length of the jib tip of 3.2 tons.

2. The new flat top tower crane offers a very competitive maximum freestanding height to reduce erection time and lower costs. Optimized for transport, these tower segments come preassembled with aluminum ladders for fast erection and increased durability.

3. It puts the operator in the lap of luxury with a fully adjustable comfort seat and joystick controls with short stroke length providing a pleasant and comfortable working environment.

4. High-Top cranes are the best choice for handling high lifting capacities.

#### Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China