



QD3060 Derrick Tower Crane without Mast Section Manufacturer Price

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QD3060 Derrick Crane
- Minimum Order Quantity: 1 set
- Price: \$88500-104000 per set
- Packaging Details: Naked packing, 1*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 20 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 10t
- Boom: 30m
- Tip. Load: 6.0t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Color: Yellow Or According To Clients Need



More Images



Product Description

QD3060 Derrick Tower Crane without Mast Section Manufacturer Price

Short Parameters

- 1.QD150(3060) Derrick Tower Crane
2. Type: fixed
3. jib length: 30m
4. tip load: 6.0t
5. max.laod: 10t@4rate, 5t@2rate.
- 6.height:75m@4rate, 150m@2rate

Specification

Rated Lifting Moment	1500KN.m
Rated Loading Capacity	10t
Max. Lifting Load	10t
Tip Load	6.0t
Max. Lifting Height	150m
Jib length / Span	30m
Working range	3 to 30m
Slewing speed	0-0.6r/min
Trolleying speed	0-10 m/min
Luffing speed	0-96 0-48 m/min
Power supply	380V/50Hz or others
Electric switch box	Schneider
Slewing bearing model	1600.45

Feature

- (1) Special design of separate-settled. Low center weight of gravity in slewing, large lifting capacity and reasonable mechanism design.
- (2) Big luffing range. The slewing radius can reach 30 m. More efficiency will come true by changing luffing range under rated load.
- (3) Three mechanisms-lifting, luffing and slewing, with satisfied performance in shifting and high efficiency, are operated easily.
- (4) With kinds of safety facilities, as limiter for lifting moment, slewing limiter and luffing limiter. Once over load happen, the facilities will turn down power automatically right away.
Also, an electronic transducer for load is fixed to cut down power when overloading appears.
- (5) Installation and disassembly is convenient. The product can be transferred to other site in short time and maintenance is very easy and convenient. All spare parts satisfy relative standards.
- (6) Electric control box is equipped to the crane which is operated easily and safely.

Control method

- (1) Pendent line control
- (2) Remote control
- (3) Cabin control
- (4) Choose any two together

Painting

- (1) Process: Sandblast, Primer, finishing paint
- (2) Color: Yellow, Red, Blue etc. (according to your demand).
- (3) Average thickness: Above 120 microns. (According to your demand).

Application

1. Shipping platforms
2. High-rise buildings
3. Construction sites

Why choose us

1. A professional tower crane supplier in China with 15 years experience
2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
3. Hydraulic self-climbing mechanism
4. Variable-frequency slewing mechanism
5. Variable-speed frequency PLC control System
6. Operation data display screen and Safety monitoring system (Black Box)
7. Various safety devices

Photos



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China