



TC6012 Self Erecting Topkit Tower Crane Double Top Slewing Type 6T Load

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: TC6012 Topkit Tower Crane
- Minimum Order Quantity: 1
- Price: \$61400-69800 per set
- Packaging Details: Naked packing, 5*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Double Top Slewing
- Load: 6t
- Boom: 60m
- Tip. Load: 1.2t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.6*1.6*2.5 M (block Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



for more products please visit us on hycmtowercrane.com

Product Description

TC6012 Self Erecting Topkit Tower Crane Double Top Slewing Type 6T Load

Shot Parameters

1. TC6012 Topkit Tower Crane
2. Type: fixed and external climbing
3. Working jib length: 60m
4. Tip load: 1.2t
5. Max. load: 6t
6. Freestanding height: 40m

Specification

Foundation	fixed or mobile
Freestanding height	40 meters
Max. height	150 meters
Max. radius	60 meters
Jib end load	1.2 t
Max. load	6 T
Drum capacity	400 meters
Lifting speed	2r=80/40/8.5 4r=40/20/4.25 m/min
Slewing speed	0.6 r/min
Trolley speed	40/20 m/min
Power line voltage	380V/50Hz (60Hz)
Counter weight	Steel-structured frame (without concrete)
Mast section	1.835 x 1.835 x 2.5 m (135*12 square steel)

The process features

- 1) Automatic submerged arc welding is adopted in the main section limbs and chord boom. It has high thermal efficiency, high penetration, high production efficiency, while reducing the pores and crack defects, increases the weld strength and the beautiful appearance.
- 2) We adopt carbon dioxide gas welding; it has heat concentrated, a small welding line, high strength and resistance to rust and crack. It can reduce stress and deformation, it has high strength and resistance to rust and crack.
- 3) Shot blasting is used for masts to strengthen the hardness of steel surface; enhance the paint adhesion and prolonging its life

Description

1. The Fixed Tower crane base fixed to the ground on a concrete foundation
2. The base is then attached to the mast sections which gives the crane its height.
3. Further the mast is attached to the slewing unit that allows the crane to slewing.
4. The horizontal jib (working arm) is the part of the crane that carries the load.
5. The counter-jib carries a counterweight while the jib suspends the load to and from the center of the crane.
6. The crane operator usually stay in the cabin at the top of the tower.
7. The lifting hook is operated by the operator using electric motors to manipulate wire rope cables through a system of sheaves which lift the building materials

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China