

QTZ5013 Hammerhead Tower Crane 2.5m Block Mast Sections 10 Story Building

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms: TT, LC
- Supply Ability:



Product Specification

Condition:	100% New
 Application: 	10 Story Building
• Туре:	Fixed With Hammer Head
• Load:	5T
• Boom:	50mts
• Tip Load:	1.3tons
• Power supply:	380V/50Hz Or According To Client's Requirements
 Mast sectionS: 	2.5m Block
Electric Box:	Schneider
Power Supply:	380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need

China

1

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

QTZ5013 Tower Crane

\$42600-47900 per set

40 sets per month

Naked packing, 5*40'HQ containers.

10 days after receiving the deposit or origin



More Images



QTZ5013 Hammerhead Tower Crane 2.5m Block Mast Sections 10 Story Building

Short Parameter

- 1.QTZ63(TC5013) Topkit Tower Crane
- 2. Type: fixed and external climbing
- 3. jib length:50m
- 4. tip load:1.1.3t

5. max.laod: 5t 6.freestanding height:35m

Specification

	QTZ63 (5013) Tower Crane
1)	50
y (T)	5
	1.3
nt (m)	35
nchorages (m)	150
nsion (m)	1.6×1.6×2.5, square tube 135×10mm
Speed (m/min)	70/35/7.0, 35/17/3.5
Motor power (kw)	18/18/5
Speed (r/min)	0.7/0.35
Motor power (kw)	2*3.7
Speed (m/min)	38.6/25.2
Motor power (kw)	1.5/2.2
Speed (m/min)	0.4
Motor power (kw)	4
	24.9
	380V/50Hz, 415/50Hz, 220V/60Hz, ect
	y (T) it (m) inchorages (m) insion (m) Speed (m/min) Motor power (kw) Speed (r/min) Motor power (kw) Speed (m/min) Motor power (kw) Speed (m/min)

Advantage

- 1. 15 years of experience in supplying all kinds of tower cranes.
- 2. Export to more than 20 countries with CE/ ISO/ GOST/ CU-TR Certifications.
- 3. Mobile and internal climbing type tower cranes are also offering.
- 4. Rost blasting and rust protection painting with advanced painting process.
- 5. Strict and experience welding line.
- 6. New designed mast, can be also used to Internal Climbing tower cranes.
- 7. Well known brand mechanism system, Schneider Electronic control system.
- 8. Engineers are available to service machinery overseas.
- 9. For long warranty: 12 months from the B/L date.
- besides, some free easy-worn spare parts are provided with the crane.

Description

1. Durable and economical, HYCM tower crane is widely used at major construction sites, lifting steel, generators, large tools and other building materials.

2. Our tower crane adopts high-end configuration and advanced technologies to ensure their high performance, safety, easy operation and maintenance.

Safety devices:

- 1): Hoist height limit
- 2): Over speed limit
- 3): Over load limit
- 4): Lifting moment limit
- 5): Slewing angle limit
- 6): Emergency stop button
- 7): Obstruction light (tip of jib, tower head)
- 8): Wind lock device.

