



TC6520 Top Slewing Tower Crane 160 foot tower could shipping to Halifax

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: TC6520 Topkit Tower Crane
- Minimum Order Quantity: 1
- Price: \$149500-154500 per set
- Packaging Details: Naked packing, 7*40;HQ containers.
- Delivery Time: 30 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 10 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Top Slewing
- Max. Load: 10 T
- Jib: 215 Feet 65 Meter
- Height: 160 Foot
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 2*2*3 M
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



Product Description

TC6520 Top Slewing Tower Crane 160 foot tower could shipping to Halifax

Description

1. TC6520 Tower Cranes are ideal for medium-sized and large construction projects, for example in industry and plant construction.
2. This Tower Cranes can handle high load capacities and have an unmistakable silhouette. The various size classes prove their worth for medium and large construction projects, for example for industrial and plant construction.
3. Tower cranes are also suitable for use on very high buildings. Our customers benefit from enormous hoisting heights and hoist speeds.

Specification

Rated Lifting Moment (KN.M)	2300
Rated Loading Capacity (t)	10
Max. Lifting Load (t)	10
Span (m)	65
Working range (m)	3 to 65
Tip Load (t)	2.0
Max. Lifting Height (m)	180
Free standing height (m)	60
Rope length (m)	500
Slewing speed (r/min)	0-0.6
Trolley peed (m/min)	0-60
Jacking-up speed (m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	61.5
Electric switch box	Schneider
Main Material (mm)	200*20 / angle steel
Mast section (m)	2*2*3 (split type)

Characteristics

- 1) Lifting multiplying factor switch-over which could achieve high speed for light load and low speed for heavy load.
 - 2) Our tower sections are exchangeable, which provide our customers more conveniences.
 - 3) We adopt to use Dual drawbars structure on lifting boom, which enables the lifting boom to be under no stress at lifting surface other than uniaxial stress, and moreover, it gets rid of the stress peak. It greatly improves the fatigue safety performance of lifting boom.
 - 4) Adopts VVVF stepless speed variation device for lifting, radius changing and slewing mechanisms, to make sure it works steadily and effectively, it also lowers the maintenance cost.
- It's lifting height is obviously increased thanks to its self-erecting and wall attached function.

It is applicable for construction of different industrial, commercial, office, and civil building lower than 120m, and becomes an ideal service-building machine at home.

Advantage

1. Export to more than 20 countries with CE/ ISO/ GOST Certifications by skilled sales team.
2. Mobile and internal climbing type tower cranes are also offering as new designed mast sections.
3. High Quality control: blasting and rust protection painting with advanced painting process. Strict and experience welding line.
4. Well known Mechanisms system and Schneider Electronic control system.
5. Engineers are available to service machinery overseas within 12 months warranty from the B/L date.
6. One set free easy-worn spare parts are provided with per set tower cranes.

Pictures





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China