



SC200 2000KG Cab Tilt Building Construction Man-Lift Passenger Hoist

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC Building Hoist
- Minimum Order Quantity: 1 set
- Price: \$25500-39900 per set
- Packaging Details: Naked packing, 1*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Electric Cable Climbing
- Cab: 2000kg
- Max. Height: 150-200 M
- Rated Speed: 33m/min
- Power supply: 380V/50Hz Or According To Client's Requirements
- Motor Power: 3*11kw Or 2*13kw
- Motor Brand: Xingxiang, Sanshang, Juli Or Other
- Mast Section Size: 650*650*1508mm Or 800*800*1508mm



More Images



Product Description

SC200 2000KG Cab Tilt Building Construction Man-Lift Passenger Hoist

Description

1. Construction Hoist is also called as Man-Lift, Temporary elevator, Builder hoist, Passenger hoist or Construction elevator.
2. This type of hoist is commonly used on large scale construction projects, such as high-rise buildings or major hospitals.
3. There are many other uses for the construction elevator. Many other industries use the buckhoist for full-time operations, the purpose being to carry personnel, materials, and equipment quickly between the ground and higher floors, or between floors in the middle of a structure.
4. There are three types: Utility to move material, personnel to move personnel, and dual-rated, which can do both. SC series lifting both material and personnel.

Specification

Model	SC200
Payload capacity	Up to 2000 kg
Speed m/min	33, 0-33, 0-46, 0-96 or others
Max. lifting height	150 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2 x 11 kw
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 1 racks	127 kg

Completed safety measures

1. Safety Governor
2. Top limit switch and Bottom limit switch
3. 3-phase switch
4. Buffer Spring
5. Mechanical lock
6. Reducing device
7. Brake pieces
8. Overload Protector
9. Leakage Protection switch
10. Emergency button
11. Terminal and Final stopping switches
12. Guard Rail

Our advantage

1. 15 years of experience in supplying new external climbing tower crane with HYCM Brand.
2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
3. Stationary/Traveling and internal climbing type tower crane are available
4. Impeller blasting/rust protection paint
5. Advanced painting process
6. Strict and experience welding line
7. New designed mast, can be used to Internal and external climbing tower crane
8. Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
9. Engineers available to service machinery overseas.
10. For warranty, it is 12 months from the B/L date. What's more, some free easy worn spare parts are provided together with the crane.

Pictures



emma1109@foxmail.com
0086 18254159408



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China