



## 1tons to 4tons Building Hoist Middle Speed Schneider Inverter Manufacturer

Our Product Introduction

for more products please visit us on [hycmtowercrane.com](http://hycmtowercrane.com)

### Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC Building Hoist
- Minimum Order Quantity: 1 set
- Price: \$23000-33800 per set
- Packaging Details: Naked packing, 1\*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



### Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Middle Speed
- Max. Load: 1-4 T
- Max. Height: 150-200 M
- Rated Speed: 0-33 Or 0-40 Or 0-45 M/min
- Power supply: 380V/50Hz Or According To Client's Requirements
- Motor Power: 2\*11kw Or 2\*3\*11 Kw
- Motor Brand: Xingxiang, Sanshang, Juli Or Other
- Mast Section Size: 650\*650\*1508 Mm



### More Images



## Product Description

### 1tons to 4tons Building Hoist Middle Speed Schneider Inverter Manufacturer

#### Our construction hoist advantage

1. Cage: Integral style cage, a whole welded steel structure, compact and sturdy. Roller, back wheel ect. own production, bearing for the best domestic bearings, Aluminum peripherals which is light, no vibration, no noise, etc. also can be designed according to customer requirements.
- Cage door: can be designed according to customer requirements into a single, double or ramp type.
2. Motor: Shuang Ma Brand configuration, warranty replacement for 2 years from leave factory date.
- Reducer: CASK Brand Gear box configuration, warranty replacement for 2 years from leave factory date.
3. Anti-fall safety device SAJ40-1.2: Shanghai Construction Institute, the domestic well-known brands
4. Electric: all Schneider, except transformers (Schneider does not produce transformers)
5. Mast section: Robot welding, applicability, 0-450 meters of buildings, flat support is one-time stamping of the U-shaped groove, brace support is 20 solid steel which toughness stronger.
- Rack own production which can be centered or biased install.
6. Paint: automatic electrophoresis paint line

#### Specification

| Specification                      | Type         | Lifting Capacity | Lifting Speed                       | Motor Power                  | VFD                          | Safety device                          |
|------------------------------------|--------------|------------------|-------------------------------------|------------------------------|------------------------------|--|
| Single cage without counter weight | SC 100 M     | 1000Kg           | 0 63m/min                           | 3×13Kw                       | 45Kw                         | SAJ 40-1.6                             |
|                                    | SC 150 M     | 1500Kg           | 0 63m/min                           | 3×15Kw                       | 55Kw                         | SAJ 40-1.6                             |
|                                    | SC 200 M     | 2000Kg           | 0 55m/min                           | 2×23Kw(87 Hz)                | 55Kw                         | SAJ 40-1.6                             |
|                                    |              |                  | 0 63m/min<br>0 72m/min              | 3×18.5Kw<br>3×19Kw(87 Hz)    | 75Kw<br>75Kw                 | SAJ 50-1.6<br>SAJ 50-1.6               |
|                                    | SC200H       | 2000Kg           | 0 80m/min                           | 3×23Kw                       | 75KW                         | SAJ50-1.6                              |
| Twin cages without counter weight  | SC 100/100 M | 1000Kg×2 EA      | 0 63m/min                           | 3×13Kw×2E A                  | 45Kw                         | SAJ 40-1.6                             |
|                                    | SC 150/150 M | 1500Kg×2 EA      | 0 63m/min                           | 3×15Kw×2E A                  | 55Kw                         | SAJ 40-1.6                             |
|                                    | SC 200/200 M | 2000Kg×2 EA      | 0 58m/min<br>0 63m/min<br>0 72m/min | 2×23Kw×2E A                  | 55Kw<br>55Kw<br>75Kw<br>75Kw | SAJ 40-1.6<br>SAJ 50-1.6<br>SAJ 50-1.6 |
|                                    |              |                  |                                     | 2×26Kw×2E A                  |                              |  |
|                                    |              |                  |                                     | 3×18.5Kw×2 EA<br>3×19Kw×2E A |                              |  |
|                                    | SC200/200H   | 2000Kg×2 EA      | 0 80m/min                           | 3×23Kw×2E A                  | 75KW                         | SAJ50-1.6                              |

#### Humanistic Design

1. Newly designed height of the cage (2.46m), which can save freight.
2. Top of the cage is made of a complete high-grade steel, so the waterproof performance is greatly improved.
3. Body of cage is made of mesh steel plate, appearance of which with special spray technology which makes cage more beautiful, can completely against rust and prolong its usage life-span.
4. Door frame is made by light weight steel shape which can make cage more stable.
5. Special embedded counterweight design. More safe and stable in.
6. Improved door handle makes the operation more easily.

#### Equipment

CNC Plasma cutting machine  
Punching machine  
Large plate bending machine  
Electrophoresis pain production line  
Cold forming machine processing line  
Robot welding

#### Picture



**Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane**



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China