



## 500 kg Small Construction Hoist Elevator with Inverter control stable speed

Our Product Introduction

for more products please visit us on hycmtowercrane.com

### Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC Building Hoist
- Minimum Order Quantity: 1 set
- Price: \$16800-19900 per set
- Packaging Details: Naked packing, 1\*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



### Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Electric Cable Climbing
- Max. Load: 0.5t
- Max. Height: 150-200m
- Rated Speed: 33m/min
- Power supply: 380V/50Hz Or According To Client's Requirements
- Motor Power: 1\*11kw
- Motor Brand: Xingxiang, Shuangma, sanshang, Juli Or Other
- Mast Section Size: 650\*650\*1508mm



### More Images



## Product Description

### 500 kg Small Construction Hoist Elevator with Inverter control stable speed

#### Short Introduction

1. Use rack-and-pinion transmission technology.
2. CNC Plasma/Flame Cutting Machine
3. Mast Section Robot welding line
4. Impeller Blasting
5. Baking painting
6. Full set safety device
7. Accepted customer's OEM

#### Specification

Model	SC50
Payload capacity	Up to 500 kg
Speed	0-33 m/min
Max. lifting height	150 m (Increased lifting height on request.)
Cage width (internal)	1 m
Cage length (internal)	1.2 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	1 x 11 kw
Safety device	Mechanical interlocking door system to guarantee the highest safety standards.
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	0.65*0.65*1.508m
Length mast section	1.508 m

#### Main Characteristic

1. The mast sections of construction hoist adopt welding robot to weld, reliable in price and elegant in appearance.
2. All the structures adopt reaming impeller blasting technology, the adhesion of surface painting is good.
3. The wall around cage can be fixed by Punched Aluminum plate, Punched zinc plate, steel wire mesh.
4. Professional manufacturer provide the transmission gear, high mechanical efficiency, extended service life, steady performance.
5. Overload protection, variety of limiter and mechanical chain device are reliable and complete, optimal safety device select SAJ30-1.2, which restrict the excessive downward movement of the cage and prevents cage falling accidents.
6. Variable-frequency construction elevator are safe, steady, comfort, start electricity is smaller than the working electricity and efficient.

#### Picture



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



[hycmtowercrane.com](http://hycmtowercrane.com)

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu

