



SJY0.5-14 Mobile Scissor Platform Load Capacity 500kg 14m Platform Height 380V Power

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or others
- Certification: ISO, CE
- Model Number: SJY0.5-14 Scissor Lift Platform
- Minimum Order Quantity: 1 set
- Price: \$5300-7200 per set
- Packaging Details: Plywood package, LCL or 20'GP, 40'HQ construction
- Delivery Time: 7-10 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 50 sets per month



Product Specification

- Condition: 100% New
- Application: Load Passengers To Aerial Work
- Type: Hydraulic System Rise
- Load: 500kg
- Platform Height: 14m
- Rated Speed: 4-6 M/min
- Power: 380v /50Hz Or Others
- Motor Power: 3 Kw
- Platform Material: High Strength Steel
- Platform Size: 2.55*1.5m
- Color: Blue, Yellow Or Others



More Images



Product Description

SJY0.5-14 Mobile Scissor Platform Load Capacity 500kg 14m Platform Height 380V Power

General Introduction of this mobile scissor lift platform

1. Load capacity: 500kg
2. Lifting height: 16m
3. Drive power: 4 pneumatic rubber tyres.
4. Applications: aerial installation, maintenance, clean at the construction sites, workshops, warehouse, hotel, airport, wharf, gas station and stadium etc.
5. Custom-made according to the requirement
6. The worker can control the scissor lift on the platform when raised by handle .
7. The worker can also control the lift on the floor by handle control

Specification

Model No.	SJY0.5-14 Scissor Lift
Type	Mobile and self rising (manpower travel, could equipt assisted travel by adding battery)
Load Capacity	500kg
Platform Height	14m
Working Height	16m
Platform size	2800*1550mm
Total size (without guardrail)	3067*1730*1810mm
Weight	2400kg
Power	3kw/380v/50Hz
Lift speed	4-6m/min
Optional	DC, Diesel or AC and DC

Function

1. High working capacity, easily pushed around, most spacious platforms for several people to work on
2. High strength steel structures, smoothly lift up and drop down, easily operated, few faults.
3. Moving method: 4 wheel and 2 wheel types are optional, it can be pneumatic rubber tyres, solid rubber tyres or polyurethane tyres.
4. Power sources: local power available at the working sites (110V, 220V, 380V, 415V), diesel engines and generators

Features

2. An ideal equipment of safe operation
3. It is characterized by great loading capacity.
4. Steady ascending and descending
5. Mobile convenient, easy to work.
6. Local voltage can be customized (110V, 220V, 380V)
7. Lift power: AC, DC or diesel available.

Safety protection

1. Explosion-proof valves: protect hydraulic pipe, anti-hydraulic pipe rupture
2. Spillover valve: It can prevent high pressure when the machine moves up. Adjust the pressure.
3. Emergency decline valve: it can go down when you meet an emergency.

Service

1. All the machines will be full tested before shipment
2. The total machine guarantee is 12 months
3. 24 Hours technical support, email, telephone or video online
4. User-friendly english manual for machine using and maintaining
5. Sereral sets wearing parts will be free for you



Electric Appliance

The control box is brand of De Li Xi, famous brand. With overheat protective device and lack of phase protection.

emma1109@foxmail.com

High strength support

High strength steel , sound construction.
Uses famous brand steel.

emma1109@foxmail.com



Hydraulic System

The lift with emergency drop valve, it can be manually controlled down when power failure.

emma1109@foxmail.com

Built-in overflow valve, can prevent high system pressure when lift working to overloading protection .



Hydraulic Tubing

The tubing uses two layers of wire mesh rubber hose. Security and stability, high temperature resistance.

emma1109@foxmail.com

More products available:

Tower Cranes

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform

---Most popular model ZLP630, ZLP800: 630KG AND 800KG

□



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China