



## 500kg SJY0.5-12 Scissor Lift Platform Hydraulic Work with Pneumatic Rubber Tyres

### Our Product Introduction

for more products please visit us on [hycmtowercrane.com](http://hycmtowercrane.com)

#### Basic Information

- Place of Origin: China
- Brand Name: HYCM or others
- Certification: ISO, CE
- Model Number: SJY0.5-12 Scissor Lift Platform
- Minimum Order Quantity: 1 set
- Price: \$4560-6350 per set
- Packaging Details: Plywood package, LCL or 20'GP, 40'HQ construction
- Delivery Time: 7-10 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 50 sets per month



#### Product Specification

- Condition: 100% New
- Application: Load Passengers To Aerial Work
- Type: With Pneumatic Rubber Tyres
- Load: 500kg
- Platform Height: 12m
- Rated Speed: 4-6 M/min
- Power: 380v /50Hz Or Others
- Motor Power: 3 Kw
- Platform Material: High Strength Steel
- Platform Size: 2600\*1500mm
- Color: Blue, Yellow Or Others
- Weight: 2260kg



#### More Images



## Product Description

### 500kg SJY0.5-12 Scissor Lift Platform Hydraulic Work with Pneumatic Rubber Tyres

#### General Introduction

1. Load capacity: 500kg
2. Platform height: 12m
3. Drive power: 4 pneumatic rubber tyres.
4. Applications: aerial installation, maintenance, clean at the construction sites, workshops, warehouse, hotel, airport, wharf, gas station and stadium etc.
5. Custom-made according to the requirement
6. The worker can control the scissor lift on the platform when raised by handle .
7. The worker can also control the lift on the floor by handle control

#### Specification

Model No.	SJY0.5-12 Scissor Lift
Type	Mobile and self rising (manpower travel, could equipt assisted travel by adding battery )
Load Capacity	500kg
Platform Height	12m
Working Height	14m
Platform size	2600*1500mm
Total size (without guardrail)	2800*1710*1850mm
Weight	2260kg
Power	3kw/380v/50Hz
Lift speed	4-6m/min
Optional	DC, Diesel or AC and DC

#### Function

1. High working capacity, easily pushed around, most spacious platforms for several people to work on
2. High strength steel structures, smoothly lift up and drop down, easily operated, few faults.
3. Moving method: 4 wheel and 2 wheel types are optional, it can be pneumatic rubber tyres, solid rubber tyres or polyurethane tyres.
4. Power sources: local power available at the working sites (110V, 220V, 380V, 415V), diesel engines and generators

#### Safety protection

1. Explosion-proof valves: protect hydraulic pipe, anti-hydraulic pipe rupture
2. Spillover valve: It can prevent high pressure when the machine moves up. Adjust the pressure.
3. Emergency decline valve: it can go down when you meet an emergency.

#### Service

1. All the machines will be full tested before shipment
2. The total machine guarantee is 12 months
3. 24 Hours technical support, email, telephone or video online
4. User-friendly english manual for machine using and maintaining
5. Sereral sets wearing parts will be free for you





#### More products available:

##### Tower Cranes

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

##### SC Construction Man and Material Elevator

- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

##### SS Building Material Lift / Hoist

- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

##### ZLP Suspended Platform

- Most popular model ZLP630, ZLP800: 630KG AND 800KG

□□□



**Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane**



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China