



OEM ZLP630 Industrial Aerial Platform 630kg 6M length 8.3mm Steel Wire Rope

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or others
- Certification: ISO, CE
- Model Number: ZLP630 Platform
- Minimum Order Quantity: 1 set
- Price: \$1910-2550 per set
- Packaging Details: pallet, LCL or 20'GP, 40'HQ construction
- Delivery Time: 7-10 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 50 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Industrial Aerial Platform
- Rated Load: 630kg
- Steel Wire Rope: 8.3mm
- Rated Speed: 9-11 M/min
- Power supply: 440V 60Hz, 380V 50Hz Or Others
- Motor Power: 2*1.5 Kw
- Platform Material: Steel, Hot Galvanized Or Aluminum
- Cable Length: 95m
- Highlight: OEM ZLP630 industrial aerial platform, 630kg suspended work platform, 6M length steel wire rope platform



More Images



Product Description

OEM ZLP630 Industrial Aerial Platform 630kg 6M length 8.3mm Steel Wire Rope

Description

It is driven by electric hoist and wire rope, running against the building facade while the suspension mechanism was erected on buildings or structures.

It is ideal for building facade construction, decoration, cleaning and maintenance. It is also widely used in elevator installing, ship building and repairing, or in other areas such as big-size tank, bridge, embankment and chimney.

ZLP series versatile knock-down platform provides workers safer, easier and more efficient platform access.

Absolutely guarantee life safety during Aerial working. Safety lock fasten the steel rope immediately once the suspended platform tilts or the steel rope slips out of the hoist; Electric control system is designed with leakage protection, over-heat protection, current overload protection and brake stop

Specification

Model No.		ZLP630
Rated load(kg)		630
Lifting speed(m/min)		9 11
Hoister model		LTD63
Motor power(kw)		2×1.5
Brake torque(N.m)		15.2
Rated stretch of front beam(mm)		1100-1700
Suspending Platform	No. of platform rack	Single rack
	No. of platform	3
	L×W×H(mm)	(1.5+2+2.5)×690×1180
Suspending mechanism(kg)		2×175 Kg
Counterweight(kg) --optional		25×40pcs
Diameter of steel rope(mm)		8.3
Voltage(v) 3PHASES		220V/380V/415V (customized)
Ambient temperature		-20 ~+40
Ambient relative humidity		≤ 90%(25)

The main Part:

1. Suspension Mechanism and Counterweight

The Height of the platform can be adjusted within 1150-1750mm with arm which can be stretched out and drawn back, it can be widely used parapet and complicated building in different height, and we can also supply customized platform to meet different requirement from the customers

2. Working Platform

Different material for different requests: Steel, Hot galvanized and Aluminum.

Various platform length for clients to choose.

3. Hoist Motor

LTD6.3 "a" shape hoist

4. Electrical Control box

Installed with international and national famous brands electrical components, our electrical control system consists of many protection devices, Such safety devices as electrical leakage protection device, automatic limited switch, overheat protection, emergency brake, current coverload proof, which make operate more easier, safer and reliable.

5. Safety Lock

When the steel wire rope is broken, blocked, slip out of the hoist or the working platform inclines, the safety lock will lock the rope within 100mm, this safety device is high advanced in China now.

Why choose us

1. A professional supplier in China with 16 years experience
2. Exported to more than 20 countries with ISO9001 Certifications
3. Variable-speed control System
4. Operation data display screen and Safety monitoring system (Black Box)
5. Various safety devices



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China