

# OEM Small SC100 Man and Material Hoist Lifter With Factory Cheap Price

## **Basic Information**

Place of Origin: China

Brand Name: HYCM or XINGDAO

Certification: CE, ISO

Model Number: SC Building Hoist

• Minimum Order Quantity: 1 set

• Price: \$19000-22800 per set

Packaging Details: Naked packing, 1\*40'HQ containers.

• Delivery Time: 15 days after receiving the deposit or origin

LC

• Payment Terms: Western Union, L/C, T/T

• Supply Ability: 40 sets per month



# **Product Specification**

• Condition: 100% New

Application: Buildings And Projects

Type: SmallLoad: 1 TonsMax. Height: 150-200 M

• Rated Speed: 33 M/min Or 0-33m/min

• Power supply: 380V/50Hz Or According To Client's

Requirements

• Motor Power: 2\*11 Kw

Motor Brand: Taichang, Jinnuoi Or Other

Mast Section Size: 650\*650\*1508mm



# More Images



#### **OEM Small SC100 Man and Material Hoist Lifter With Factory Cheap Price**

#### Simple parameter

Model: SC100 Single cage construction hoist
Rated load: 1000kg (1ton)
Raged passengers: 10
Motor power: 2\*11kw
Rated lifting speed:33 or 0-33 m/min
Mast section size: 0.65\*0.65\*1.508m or 0.8\*0.8\*1.508m
Cage size: 3.2\*1.5\*2.2m or according to clients needs

Cage size: 3.2\*1.5\*2.2m or according to clients needs
Power supply: 380V/50Hz, 220V/60Hz or others
Max. Lifting height: 150m-200m
With all standard accessories

#### Specification

Model	SC100 single cage construction hoist
Payload capacity	Up to 1000 kg
Speed (m/min)	33 or 0-33 or others
Max. lifting height	150-200 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2x11 kw
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 1 racks	127 kg

#### **Parts**

#### 1. Driver Cabin

The driver cabin of our construction hoist is constructed from hot dip galvanized plates with surface powder spraying treatment which ensure superior corrosion resistance. It has fan that can improve driver's working environment.

#### 2. Gear Train

The new back gear is lengthened by one time at the stationary bearing end where it is equipped with locating taper pin to improve stress state and avoid loosening of back gear that will affect gear backlash.

The parts such as bear gear, idler wheel, etc. that have influence on running stability are improved to enhance machining and manufacturing precision. All of them will experience thermal refining treatment and galvanizing treatment after that, thus showing excellent durability. Case door pulley and cable pulley are made from nylon material which can prolong their life time and effectively reduce noise.

### Picture



#### More products available:

#### **Tower Cranes**

- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

#### SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

# **ZLP Suspended Platform**







# Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane







hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China