

New QD80 Derrick Crane to Disassebly Inner Tower Crane with 8t and 30m Boom

Basic Information

- Place of Origin:
- Brand Name:

China HYCM

CE, ISO

LC

QD80 Derrick Crane

\$47500-52200 per set

Western Union, L/C, T/T

10 sets per month

Naked packing, 1*40'HQ containers.

30 days after receiving the deposit or origin

- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Condition:
- Application:
- Type:
- Load Capacity:
- Boom:
- Height:
- Power:
- Color:

100% New
Disassebly Inner Tower Crane
Fixed With Tower Head
8t
30m
150m
380v/50hz

Yellow Or According To Clients Need



More Images



New QD80 Derrick Crane to Disassebly Inner Tower Crane with 8t and 30m Boom

Short Parameters

1.QD80(3023) Derrick Tower Crane 2. Type: fixed 3. jib length: 30m 4. tip load: 2.3t 5. max.laod: 8t 6.height:150m

Specification

QD3023 Derrick Crane Specification		
Rated Lifting Moment	800KN.m	
Rated Loading Capacity	8t	
Max. Lifting Load	8t	
Tip Load	2.3t	
Max. Lifting Height	150m	
Jib length / Span	30m	
Working range	3 to 30m	
Slewing speed	0-0.6r/min	
Trolleying speed	0-10 m/min	
Luffing speed	0-80 0-40 m/min	
Power supply	380V/50Hz or others	
Electric switch box	Schneider	
Slewing bearing model	1250.45	

Description of Derrick Crane

The derrick crane was conceived as a specialist disassemble crane for stripping down cranes on tall buildings, bridge pylons and telecommunication towers.

The dimensions and weights of all individual parts on the new crane are therefore designed to enable them to be dismantled with the aid of a very small hoist and removed via lift shafts in buildings.

Feature

(1) Reasonable structure for less costing and maintenance.

- (2) Favorable performance to improve your working capacity.
- (3) Smooth starting and stopping to improve you security sense.
- (4) Low noise, commodious cabin and good view can make you happiness operating and accurate operating.
- (5) Credible electric parts to guarantee the crane safety in operating.

Safety device

- (1) Weight overload protection device
- (2) Lifting height limit device
- (3) Voltage lower protection function
- (4) Phase sequence protection function
- (5) Emergency stop function

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Introduction

- 1. The Derrick cranes is fixed to the roof.
- 2. The base is then attached to the slewing unit that allows the crane to sewing.
- 3. On top of the slewing unit there are two main parts which are: the long jib, shorter counter-jib,
- 4. The long jib is the part of the crane that carries the load.
- 5. The crane operator either sits in a cab at the top of the tower or controls the crane by radio remote control from the ground. 6. The lifting hook is operated by the crane operator using electric motors to manipulate wire rope cables through a system of sheaves.

Why chose US

Good Quality: Gotten certification of ISO

Best price: Best offer with suitable payment terms.

Good Sale Service: Technician provided to assistant installment, ect.(Buyer bear the fee).

Delivery on Time: Report order progress. Make sure Delivery on time.

<u>Warranty:</u> Provide a warranty of 12 months from the bill date.

Photos

for more products please visit us on hycmtowercrane.com



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China