




SC200/200 Construction Hoist of a Second Elevator Cage 2000kg Per Cage Load

Our Product Introduction

for more products please visit us on hycmtowercrane.com


Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC200/200 Passenger Elevator
- Minimum Order Quantity: 1 set
- Price: \$26500-29600 per set
- Packaging Details: Naked packing, 1*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month




Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: With SRIBS Anti-fall Safety Device
- Load: 2000kg Per Cage
- Height: 110 Meters
- Speed: 33 M/min Or Others
- Power supply: 380V/50Hz Or According To Client's Requirements
- Motor Power: 2*3*11 Kw Or Others
- Motor Brand: Shuangma, Xingxiang, Sanshang, Juli Or Other
- Mast Section Size: 650*650*1508 Mm



More Images



Product Description

SC200/200 Construction Hoist of a Second Elevator Cage 2000kg Per Cage Load

Description

The Elevator is designed for passenger and materials transport. It offers, efficiency, safety, reduced energy consumption and low operating costs, making it the ideal hoist solution for construction and rental companies. A modern microprocessor hoist control system with stop-next-landing control allows for simple operation and ease of use. While a hoist capacity of 4,000 kg offers increased transport capacity at a low cost. With a larger hoist car, higher speeds and increased lifting heights, the SC200/200 is the perfect hoist solution for high-demand and high-rise construction, new build construction, refurbishment, chimney, offshore and bridge construction.

Specification

Model	SC200/200 - Ordinary
Payload capacity	Up to 2 x 2,000 kg
Speed	33m/min or others
Max. lifting height	150 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2 x 3 x 11 kw or others
Safety device	Mechanical interlocking door system to guarantee the highest safety standards.
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 2 racks	158 kg

Humanistic Design

1. Newly designed height of the cage (2.46m), which can save freight.
2. Top of the cage is made of a complete high-grade steel, so the waterproof performance is greatly improved.
3. Body of cage is made of mesh steel plate, appearance of which with special spray technology which makes cage more beautiful, can completely against rust and prolong its usage life-span.
4. Door frame is made by light weight steel shape which can make cage more stable.
5. Special embedded counterweight design. More safe and stable in.
6. Improved door handle makes the operation more easily.

Other models of SC construction hoist

SC50, SC100, SC200, SC100/100 Single and Double Cage with or without Cab for your choice

Picture





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China