

QD80 Derrick Crane Lift Building Materials and Tower Crane Parts

Basic Information

- Place of Origin:
- Brand Name:
- Certification:

China HYCM

CE, ISO

LC

QD80 Derrick Crane

\$53400-55000 per set

Western Union, L/C, T/T

10 sets per month

Naked packing, 1*40'HQ containers.

30 days after receiving the deposit or origin

- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

ema tuga tema u com

Product Specification

- Condition:Application:
- Type:
- Max.Load:
- Lifting Boom:
- Tip Load:
- Power:
- Color:

100% New
Lift Building Materials And Tower Crane Parts
Fixed With Tower Head
8tons
30mts
2.3tons
380v/50hz Or Others
Yellow Or According To Clients Need



More Images



QD80 Derrick Crane Lift Building Materials and Tower Crane Parts

Short Parameters

1.QD80(3023) Derrick Tower Crane 2. Type: fixed 3. jib length: 30m 4. tip load: 2.3t 5. max.laod: 8t

6.height:150m or others according to clients needs

Specification

QD3	023 Derrick Crane Specification
Rated Lifting Moment	800KN.m
Rated Loading Capacity	8t
Max. Lifting Load	8t
Tip Load	2.3t
Max. Lifting Height	150m
Jib length / Span	30m
Working range	3 to 30m
Slewing speed	0-0.6r/min
Trolleying speed	0-10 m/min
Luffing speed	0-80 0-40 m/min
Power supply	380V/50Hz or others
Electric switch box	Schneider
Slewing bearing model	1250.45

Description of Derrick Crane

The derrick crane was conceived as a specialist disassemble crane for stripping down cranes on tall buildings, bridge pylons and telecommunication towers.

The dimensions and weights of all individual parts on the new crane are therefore designed to enable them to be dismantled with the aid of a very small hoist and removed via lift shafts in buildings.

Feature

(1) Reasonable structure for less costing and maintenance.

- (2) Favorable performance to improve your working capacity.
- (3) Smooth starting and stopping to improve you security sense.
- (4) Low noise, commodious cabin and good view can make you happiness operating and accurate operating.
- (5) Credible electric parts to guarantee the crane safety in operating.

Safety device

- (1) Weight overload protection device
- (2) Lifting height limit device
- (3) Voltage lower protection function
- (4) Phase sequence protection function
- (5) Emergency stop function

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Introduction

- 1. The Derrick cranes is fixed to the roof.
- 2. The base is then attached to the slewing unit that allows the crane to sewing.
- 3. On top of the slewing unit there are two main parts which are: the long jib, shorter counter-jib,
- 4. The long jib is the part of the crane that carries the load.
- 5. The crane operator either sits in a cab at the top of the tower or controls the crane by radio remote control from the ground. 6. The lifting hook is operated by the crane operator using electric motors to manipulate wire rope cables through a system of sheaves.

Why chose US

Good Quality: Gotten certification of ISO

Best price: Best offer with suitable payment terms.

Good Sale Service: Technician provided to assistant installment, ect.(Buyer bear the fee).

Delivery on Time: Report order progress. Make sure Delivery on time.

<u>Warranty:</u> Provide a warranty of 12 months from the bill date.

for more products please visit us on hycmtowercrane.com





0086-18254159408

emma1109@foxmail.com

log hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China