

10 ton 65m Boom Tower Crane Construction Building Self Erecting Hammer Head Type

Basic Information

• Place of Origin: China

Brand Name: HYCM TOWER CRANE
Certification: CE, ISO, GOST, CU-TR
Model Number: TC6515 Topkit Tower Crane

Minimum Order Quantity:

• Price: \$105000-120000 per set

Packaging Details: Naked packing, 6*40'HQ or 7*40;HQ

containers.

• Delivery Time: 45 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 10 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And ProjectsType: Self Erecting Hammer Head

Load: 10 TonBoom: 65mCapacity: 1.5 T

• Power supply: 380V/50Hz Or According To Client's

Requirements

• Mast section: 1.835*1.835*2.5m Or 2*2*3m

Electric Box: Schneider

• Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need



More Images



Product Description

10 ton 65m Boom Tower Crane Construction Building Self Erecting Hammer Head Type

Features

1) Working Radius (m): 65 2) Max. Load Capactiy (T): 10

3) Tip Load (T): 1.5

4) Mast Section dimension (m): 1.835×1.835×2.5 or 2*2*3m

5) Hoisting Mechanism Speed (m/min): 0-100 0-50

6) Motor power (kw): 45kw

7) Slewing Mechanism Speed (r/min): 0-0.6

8) Motor power (kw): 5.5×2

9) Trolleying Mechanism Speed (m/min): 0-60

10) Motor power (kw): 5.5

Specification

Model		QTZ125 (6515) Tower Crane
Working Radius (m)		65
Max. Load Capacity (T)		10
Tip Load (T)		1.5
Free standing height (m)		50
Max. Height with anchorages (m)		180
Mast Section dimension (m)		1.835×1.835×2.5, two angle steel with rib 125×12mm
Hoisting Mechanism	Speed (m/min)	0-100 0-50
	Motor power (kw)	45
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	2*5.5
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		61.5
Power Supply		380V/50Hz, 220V/60Hz or others

Advantage

1. Automatic impeller blasting and spraying assembly line

Adopt the world first-class automatic spraying assembly line. The large structure parts are dealt with impeller blasting before spraying. That remove steel surface oxides and welding spatters effectively, eliminates the internal stress producing in welding process, increases the parts' anti-figure strength and steel surface hardness, increases painting adhesion and prolong the service life of the product maximizes efficiency and saves energy.

2. Strict quality examination

The strict quality test, raw material test, test of welding, checking welding quality of appearance, assembly and adjustment of jib, tower head and pivot in factory.

3.We have professional packing person to pack and put the tower crane in the container or on to the truck.

Introduction

TC6515 Tower Cranes are ideal for medium-sized and large construction projects, for example in industry and plant construction.

Customers around the world rely on our top-slewing cranes for major building projects. The intelligent high-performance drive units ensure high handling capacities and thus enhance efficiency.

The modular design means that top-slewing cranes can adjust to any specific requirement. We offer customers rapid erection and bespoke solutions.

Tower cranes are also suitable for use on very high buildings. Our customers benefit from enormous hoisting heights and hoist speeds.

Safety Device for hammerhead Tower Crane

- 1. 3 obstacle lights
- 2. Height limiter
- 3. Slewing limiter
- 4. Range/ trolley limiter
- 5. Weight limiter
- 6. Moment limiter
- 7. Anemometer and block box(optional)









emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China