

Hammerhead Tower Crane Lifting Capacity10 Tons Height 50 Meters Jib 60 Meters

Basic Information

Place of Origin: China

Brand Name: HYCM TOWER CRANE
 Certification: CE, ISO, GOST, CU-TR
 Model Number: QTZ125(6018) Tower Crane

Minimum Order Quantity:

• Price: \$103000-116500 per set

Packaging Details: Naked packing, 6*40'HQ or 7*40;HQ

containers.

• Delivery Time: 30 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

Supply Ability: 20 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And Projects

Type: Hammerhead
Lifting Capacity: 10 Tons
Jib: 60 Meters
Height: 50 Meters

• Power supply: 380V/50Hz Or According To Client's

Requirements

Mast section: 1.835*1.835*2.5m Or 2*2*3m

Electric Box: Schneider

• Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need



More Images



Product Description

Hammerhead Tower CraneLifting Capacity10 Tons Height 50 Meters Jib 60 Meters

Features

QTZ125(6018) hammerhead tower crane

Fixed / stationary tower crane

Max. load: 10ton Tip load: 1.8ton Jib length: 60m

CE, ISO, GOST, CU-TR certificates

Specification

Model		QTZ125(6018)
Working Radius (m)		60
Max. Load Capactiy (T)		10
Tip Load (T)		1.8
Free Height Under Hook (m)		50
Max. Height with anchorages (m)		180
Mast Section dimension (m)		1.835×1.835×2.5 or 2*2*3
Hoisting	Speed (m/min)	0-100 0-50
Mechanism	Motor power (kw)	45kw
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	5.5×2
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		61.5 (not includes jacking-up system)
Power Supply		380V/50Hz
Base type		Well shaped base/cross base/ base with ballast
No. of containers		7 x 40'HQs
		1) Anemometer 2) Air condition in cabin 3) Block box 4) Remote control

Main Features

This tower crane with tower head which connects with jib and counter-jib by tie bars, gives tower crane stronger structure and stable working condition. Besides, It's the most popular type at home and abroad with cheap cost. Four Mechanisms (Hoisting mechanism, Slewing mechanism, trolleying mechanism and hydraulic climbing mechanism) work together to control the tower crane operation.

Equipped with full safety device to avoid over-weight loading, over-speed and over-torque, so that it is with good speed-control capacity, satisfactory operating stability and high work efficiency.

They can be widely used for construction of high-rise buildings, bridge and tower-like buildings.

Why choose us

- 1. A professional tower crane supplier in China with 15 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

We accept OEM or redesign according to your detail requirements. Welcome to visit us at your free time.

Pictures









Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane







hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China