

Secondary Derrick Crane QD3015 OEM 100M Working Height Load 4tons

Basic Information

Place of Origin: China
Brand Name: HYCM
Certification: CE, ISO

Model Number: QD3015 Secondary Derrick Crane

• Minimum Order Quantity: 1 set

• Price: \$39000-43000 per set

Packaging Details: Naked packing, 1*40'HQ containers.

• Delivery Time: 25 days after receiving the deposit or origin

LC

Payment Terms: Western Union, L/C, T/T
 Supply Ability: 40 sets per month



Product Specification

Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Small Lifting Bar

Load: 4tonsWorking Height: 100MTip Load: 1.5tons

Power supply: 380V/50Hz Or According To Client's

Requirements

After Sale Service: Engineers Available To Service Overseas
 Color: Yellow Or According To Clients Need

• Highlight: Secondary Derrick Crane 100M working height,

Derrick Crane OEM 4tons load capacity, QD3015 Derrick Crane with warranty



More Images



Product Description

Secondary Derrick Crane QD3015 OEM 100M Working Height Load 4tons

Description

- 1. The Derrick cranes is fixed to the roof.
- 2. The base is then attached to the slewing unit that allows the crane to sewing.
- 3. On top of the slewing unit there are two main parts which are: the long jib, shorter counter-jib,
- 4. The long jib is the part of the crane that carries the load.
- 5. The crane operator either sits in a cab at the top of the tower or controls the crane by radio remote control from the ground.
- 6. The lifting hook is operated by the crane operator using electric motors to manipulate wire rope cables through a system of sheaves.

Specification

opcomoditori	
QD3015 Derrick Crane Specification	
Rated Lifting Moment	600KN.m
Rated Loading Capacity	4t
Max. Lifting Load	4t
Tip Load	1.5t
Max. Lifting Height	200m
Jib length / Span	30m
Working range	3 to 30m
Slewing speed	0-0.6r/min
Trolleying speed	0-10 m/min
Luffing speed	A4=32/16/3.5 m/min
Power supply	380V/50Hz or others
Electric switch box	Schneider
Slewing bearing model	1220.32

Advantages of Derrick Crane

- Operations at great heights
- ·Adaptable universal machine for heavy loads
- ·Adaptable support base
- Compact component dimensions
- ·Rapid self-disassembly
- ·Maximum weight of individual transportation units

Service of of Derrick Crane

- a. Rapid response to any inquiries and 24 hours on-line service.
- b. Competitive price which directly from facotry. Welcome to visit us.
- c. Professional inspection department to guarantee quality.
- d. Engineers will go to construction site for guiding the installation and test-running for first time if clients needs.
- e. 12 months super long time guarantee warranty.

RΔQ

1. Are you a manufacturer or a trading company?

We are as a professional manufacturer / factory since 2002 year for 15 years.

2. What is your advantage?

- 1) We are a manufacturer, so the price is more competitive than the trading company.
- 2) It is more effective to communicate with the factory, saving more time for you.
- 3) Timely after sales service
- 4) We also produce other construction machinery such as construction hoists, derrick cranes and ZLP Suspended Platform to meet your requirements.

3. How do you guarantee your product quality?

We have our professional testing department, and will test the machine all the progress, and will test it after finished and before delivery.

4. I plan to label our logo on your products, is that possible?

Sure it is ok. OEM is available for us. Just send your logo, brand name or picture to us.

5. How about the warranty period?

The warranty will be one year from the date of shipment. Any detected parts during this period caused by the quality of products will be replaced by seller free of cost (exclude wear and tie parts), improper operation and other man made reasons are excluded.

Photo of of Derrick Crane





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane







hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China