

# 50m Boom Length Manufacturers Dwg Tower Crane TC5010 5000kg Load Capacity

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



## **Product Specification**

Condition:	100% New	
<ul> <li>Application:</li> </ul>	Buildings And Projects	
• Туре:	Fixed With Tower Head	
<ul> <li>Load Capacity:</li> </ul>	5000kg	
<ul> <li>Boom Length:</li> </ul>	50m	
• Tip. Load:	1.0 T	
<ul> <li>Power supply:</li> </ul>	380V/50Hz Or According To Client's Requirements	
<ul> <li>Mast section:</li> </ul>	1.6*1.6*2.5 M	
Color:	Yellow Or According To Clients Need	
<ul> <li>Control System:</li> </ul>	Normal One	

China

1

LC

TT, LC

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

TC5010 Tower Crane

\$39000-42000 per set

40 sets per month

containers.

Naked packing, 3\*40'HQ+1\*20'GP

10 days after receiving the deposit or origin



## More Images



for more products please visit us on hycmtowercrane.com

### **Product Description**

50m Boom Length Manufacturers Dwg Tower Crane TC5010 5000kg Load Capacity

#### **Short Parameter**

- 1. Model: Double slewing QTZ50(TC5010) Topkit Tower Crane
- 2. Type: fixed and external climbing
- 3. jib length: 50m
- 4. tip load: 1.0t
- 5. max.laod: 5t
- 6.freestanding height:30m

#### Service

- a. Rapid response to any inquiry(within 3 hours) and 24 hours on-line service.
- b. Competitive price which directly work with facotry. Welcome to visit us.
- c. Professional inspection department to guarantee quality.
- d. Engineers will go to construction site for guiding the installation and test-running for first time.
- e. Easy-worn Spare parts is free supplied along with the tower crane.
- f. 12 months super long time guarantee period.

#### Specification

Model		QTZ50 (TC5010) Tower Crane	
Туре		Fixed and external climbing type	
Working Radius (m)		50	
Max. Load Capacity (T)		5	
Tip Load (T)		1.0	
Freestanding height (m)		30	
Max. Height with anchorage (m)		120	
Mast Section dimension (m)		1.6×1.6×2.5, Square 135×10mm	
Hoisting Mechanism	Speed (m/min)	(a=2) 64.15/32.57/7.0 (a=4) 32.14/15.60/3.5	
	Motor power (kw)	15/15/4	
Slewing Mechanism	Speed (r/min)	0.70/0.35	
	Motor power (kw)	3.7*2	
Trolleying Mechanism	Speed (m/min)	38.6/25.2	
	Motor power (kw)	2.2/1.5	
Jacking-up System	Speed (m/min)	0.4	
	Motor power (kw)	4	
Total Power (kw)		24.9	
Power Supply		380V/50Hz or according to clients needs	

#### Safety Features

1. Overload protection: If the material is over the capacity, the crane will give a sharp warning for protection itself 2. Emergency brake: If the operation staff encounter some emergency situation, we could start the emergency brake system to protection the related treasure.

3. Control Method: Room control or remote control to avoid any injure to the operation staff

4. Main lifting motor: with thermal protection and currency protection

#### **Our Service**

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our qualitycontrol manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

for more products please visit us on hycmtowercrane.com

Other types tower cranes, topless and luffing type are also available, besides, we accept OEM according to clients needs.



