

QTZ5010 Tower Kren 5t Max.load 50m Boom Specifications 30m Free Height

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition:	100% New	
 Application: 	Buildings And Projects	
• Type:	Hammer Head	
• Max. Load:	5t	
• Boom:	50m	
Free Height:	30m	
• Power supply:	380V/50Hz Or According To Client's Requirements	
 Mast section: 	1.6*1.6*2.5 M	
Color:	Yellow Or According To Clients Needs	
Control System:	Normal One	

China

1

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

QTZ5010 Tower Kren

\$39000-42000 per set

40 sets per month

containers.

TT, LC

Naked packing, 3*40'HQ+1*20'GP

25-35 days after receiving the deposit



More Images



Our Product Introduction

QTZ5010 Tower Kren 5t Max.load 50m Boom Specifications 30m Free Height

Short Parameter

- 1. Double slewing QTZ50(TC5010) Topkit Tower Crane
- 2. Type: fixed and external climbing
- 3. jib length: 50m
- 4. tip load: 1.0t
- 5. max.laod: 5t

6.freestanding height:30m

Service

- a. Rapid response to any inquiry(within 3 hours) and 24 hours on-line service.
- b. Competitive price which directly work with facotry. Welcome to visit us.
- c. Professional inspection department to guarantee quality.
- d. Engineers will go to construction site for guiding the installation and test-running for first time.
- e. Easy-worn Spare parts is free supplied along with the tower crane.
- f. 12 months super long time guarantee period.

Specification

opeomodilon		
Model		QTZ50 (TC5010) Tower Crane
Туре		Fixed and external climbing type
Working Radius (m)		50
Max. Load Capacity (T)		5
Tip Load (T)		1.0
Freestanding height (m)		30
Max. Height with anchorage (m)		120
Mast Section dimension (m)		1.6×1.6×2.5, Square 135×10mm
Hoisting Mechanism	Speed (m/min)	(a=2) 64.15/32.57/7.0 (a=4) 32.14/15.60/3.5
	Motor power (kw)	15/15/4
Slewing Mechanism	Speed (r/min)	0.70/0.35
	Motor power (kw)	3.7*2
Trolleying	Speed (m/min)	38.6/25.2
Mechanism	Motor power (kw)	2.2/1.5
Jacking-up	Speed (m/min)	0.4
System	Motor power (kw)	4
Total Power (kw)		24.9
Power Supply		380V/50Hz or according to clients needs

Safety Features

1. Overload protection: If the material is over the capacity, the crane will give a sharp warning for protection itself 2. Emergency brake: If the operation staff encounter some emergency situation, we could start the emergency brake system to protection the related treasure.

3. Control Method: Room control or remote control to avoid any injure to the operation staff

4. Main lifting motor: with thermal protection and currency protection

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our qualitycontrol manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Other types tower cranes, topless and luffing type are also available, besides, we accept OEM according to clients needs.

Loading Containers Pictures

for more products please visit us on hycmtowercrane.com

