

Cheaper SC100 Material Elevator 1000KG Load Integrate Inverter Control Low Speed

Basic Information

- Place of Origin:
- Brand Name:
- Certification: CE, ISO

China

AVITT or others

SC100 Construction Elevator

Naked packing, 1*40'HC containers For

15-25 days after receiving the deposit

\$17800-22800 per set

SC100 Material Elevator

Western Union, L/C, T/T

40 sets per month

- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

100% New Condition: Application: **Buildings And Projects** SINGLE CAGE • Type: 1000kg Load: • Speed: Inverter Control 380V/50Hz Or According To Client's • Power supply: Requirements • Motor Power: 2*11 Kw Or Others Motor Brand: Torui, Xingxiang, Taichang LSZ Or Other • Mast Section Size: 650*650*1508mm

Our Product Introduction

Cheaper SC100 Material Elevator 1000KG Load Integrate Inverter Control Low Speed

Simple parameter

Model: SC100 Single cage construction hoist Rated load: 1000kg (1ton) Raged passengers: 10 Motor power: 2*11kw Rated lifting speed:33 or 0-33 m/min Mast section size: 0.65*0.65*1.508m or 0.8*0.8*1.508m Cage size: 3.2*1.5*2.2m or according to clients needs Power supply: 380V/50Hz, 220V/60Hz or others Max. Lifting height: 250m With all standard accessories

Specification

Model	SC100 single cage construction hoist
Payload capacity	Up to 1000 kg
Speed (m/min)	0-33 or others
Max. lifting height	150-200 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2*11 kw or 2*13kw
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 1 racks	127 kg

Parts

for more products please visit us on hycmtowercrane.com

1. Driver Cabin

The driver cabin of our construction hoist is constructed from hot dip galvanized plates with surface powder spraying treatment which ensure superior corrosion resistance. It has fan that can improve driver's working environment.

2. Gear Train

The new back gear is lengthened by one time at the stationary bearing end where it is equipped with locating taper pin to improve stress state and avoid loosening of back gear that will affect gear backlash.

The parts such as bear gear, idler wheel, etc. that have influence on running stability are improved to enhance machining and manufacturing precision. All of them will experience thermal refining treatment and galvanizing treatment after that, thus showing excellent durability. Case door pulley and cable pulley are made from nylon material which can prolong their life time and effectively reduce noise.

Accept OEM type

Picture



More products available: Tower Cranes

---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.

---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.

---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.

---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform



No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China