

QTZ100 Topless Tower Crane 198ft Boom PT6013 Model Cheaper Factory Cost

Our Product Introduction

for more products please visit us on hycmtowercrane.com


Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: PT6013 Topless Tower Crane
- Minimum Order Quantity: 1
- Price: \$78500-86300 per set
- Packaging Details: Naked packing, 6*40'HQ+1*20'GP containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 30 sets per month



Product Specification

- Application: Buildings And Projects
- Type: Fixed
- Max. Load: 6tons
- Boom: 198ft
- Cost: Cheaper Factory
- Mast section: 1.835*1.835*2.5m (Block Type)
- Main Chord: 135*12mm (square Tube)
- Color: Yellow, Green Or Others



More Images



Product Description

QTZ100 Topless Tower Crane 198ft Boom PT6013 Model Cheaper Factory Cost

Performance parameters

- Max. jib length: 60 m
- Max. lifting capacity: 6 t
- Tip load: 1.3 t
- Max. lifting moment: 1000 KN.M
- Max. free-standing height: 45 m
- Max. working height of anchored crane: 180 m
- Types of tower crane: stationary crane and outside climbing type. Mobile and inner climbing type are available

Specification

Type	Topless or Flat top no head
Max. Lifting Load (t)	6
Tip Load (t)	1.3
Max. Lifting Height with anchorage (m)	150
Free standing height (m)	45
Rope length (m)	400
Span (m)	60
Working range (m)	3 to 60
Slewing speed (r/min)	0.6
Trolley speed (m/min)	40/20
Jacking-up speed (m/min)	0.4
Counter jib length (m)	15.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (KW)	46.2
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2)0-80; (a=4)0-40
Mast section (m)	1.835*1.835*2.5m (135*12mm square steel)

Our advantage

- 19 years of experience in supplying new external climbing tower crane with HYCM Brand.
- Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
- Stationary/Traveling and internal climbing type tower crane are available
- Impeller blasting/rust protection paint
- Advanced painting process
- Strict and experience welding line
- New designed mast, can be used to Internal and external climbing tower crane
- Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
- Engineers available to service machinery overseas.
- For warranty, it is 12 months from the B/L date. What's more, some free easy worn spare parts are provided together with the crane.

Why choose us

- A professional tower crane FACTORY supplier in China with 19 years experience
- Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- Hydraulic self-climbing mechanism
- Variable-frequency slewing mechanism
- Variable-speed frequency PLC control System
- Operation data display screen and Safety monitoring system (Black Box)
- Various safety devices

Components

Mast: the main supporting tower of the crane. It is made of steel trussed sections that are connected together during installation.

Slewing unit: the slewing unit sits at the top of the mast. This is the engine that enables the crane to rotate.

Operating cabin: the operating cabin sits just above the slewing unit. It contains the operating controls.

Jib: the jib, or operating arm, extends horizontally from the crane. A "luffing" jib is able to move up and down; a fixed jib has a rolling trolley that runs along the underside to move goods horizontally.

Hook: the hook (or hooks) is used to connect the material to the crane. It hangs at the end of thick steel cables that run along the jib to the motor.

Weights: Large concrete counterweights are mounted toward the rear of the mast, to compensate for the weight of the goods lifted.

Load Container Photos



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China