

CFPT039ZP Self Propelled Mini Scissor Type Aerial Work Platform Electric Drive

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition:	100% New	
 Application: 	Load Passengers To Aerial Work	
• Type:	With 4 Wheels	
• Load:	240kg	
 Working Height: 	5.9m	
 Lifting/Descend Speed: 	34/28 Sec	
• Lifting Motor/Drive Motor:	24/0.8 V/kw	
Battery:	2x12/105 V/Ah	
Platform Material:	High Strength Steel	
 Platform Size: 	1340x700 Mm	
Color:	Orange,blue, Yellow Or Others	

China

ISO,CE

Platform

container

7-15 days

\$6900-7200 per set

Western Union, L/C, T/T

80 sets per month

HYCM, CHUFENG or others

CFPT039ZP self propelled mini Scissor Lift

Plywood package, LCL or 20'GP, 40'HC



Our Product Introduction

CFPT039ZP Self Propelled Mini Scissor Type Aerial Work Platform Electric Drive

General Introduction of this mini scissor lift platform

- 1. Load capacity: 240kg
- 2. Lifting height: 5.9m
- 3. Applications: aerial installation, maintenance, clean at the construction sites, workshops, warehouse, hotel, airport, wharf,
- gas station and stadium etc. 4. Custom-made according to the requirement
- 5. The worker can control the scissor lift on the platform when raised by handle .
- 6. The worker can also control the lift on the floor by handle control

Specification

Parameter	Unit	CFPT039ZP
Rated Load Capacity	Kg	240
Extended platform load	Kg	105
Max. working height	m	5.8
Max. platform height	m	3.9
Length (L)	mm	1470
Width (W)	mm	760
Height(guardrail unfolded)	mm	2030
Height(guardrail folded)	mm	1730
Platform size	mm	1340x700
Platform extended	mm	600
Ground clearance (Lower)	mm	60
Ground clearance (Raised)	mm	16
Wheel base	mm	1085
Min. Turning radius	mm	0.4
(inner wheels)		
Min. Turning radius	mm	1550
(outer wheels)		
Lifting motor/Drive motor	V/Kw	24/0.8
Travel speed(Lower)	Km/h	3.5
Travel speed(Raised)	Km/h	0.5
Lifting/Descend speed	sec	34/28
Battery	V/Ah	2x12/105
Charger	V/A	24/15
Grade ability	%	25
Max. working inclination		1.5/3
Tyre size	mm	Ф230x80
Overall weight	Kg	890

Standard equipment

Proportional controls Self-lock gate on platform Extension Platform Drivable at full height Non marking tyre 2WD Automatic brakes system Emergency lowering system Emergency stop button Tubing explosion-proof system Onboard diagnostic system Tilt sensor with alarm All Motion Alarm Horn Hour meter Safety brackets Forklift pockets Charger protection Flashing beacon Folding guardrails Automatic pothole protection

Options

Overload sensor with alarm AC power on the platform Platform work lights Airline to the platform Platform anti-collision switch

Service

1. All the machines will be full tested before shipment

2. The total machine guarantee is 12 moths



More products available: Tower Cranes

---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t. ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.

---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.

---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m.

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.