



CFPT1214 Self Propelled Scissor Lifts Hydraulic Drive Safe Working Platform

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM, CHUFENG or others
- Certification: ISO, CE
- Model Number: CFPT1214 self propelled Scissor Lift Platform
- Minimum Order Quantity: 1 set
- Price: \$10000-14500 per set
- Packaging Details: Plywood package, LCL or 20'GP, 40'HC container
- Delivery Time: 10-20 days
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 80 sets per month



Product Specification

- Condition: 100% New
- Application: Load Passengers To Aerial Work
- Type: Hydraulic Drive
- Load: 320kg
- Working Height: 14m
- Lifting/Descend Speed: 60/50 Sec
- Lifting Motor/Drive Motor: 24/4.5 V/kw
- Battery: 4x12/300 V/Ah
- Platform Material: High Strength Steel
- Platform Size: 2270x1120 Mm
- Color: Orange, blue, Yellow Or Others



for more products please visit us on hycmtowercrane.com

Product Description

CFPT1214 Self Propelled Scissor Lifts Hydraulic Drive Safe Working Platform

General Introduction of this mini scissor lift platform

1. Load capacity: 320kg
2. Lifting height: 13.8m
3. Applications: aerial installation, maintenance, clean at the construction sites, workshops, warehouse, hotel, airport, wharf, gas station and stadium etc.
4. Custom-made according to the requirement
5. The worker can control the scissor lift on the platform when raised by handle .
6. The worker can also control the lift on the floor by handle control

Specification

Parameter	Unit	CFPT1214
Rated Load Capacity	Kg	320
Extended platform load	Kg	113
Max. working height	m	13.8
Max. platform height	m	11.8
Length (L)	mm	2480
Width (W)	mm	1190
Height(guardrail unfolded)	mm	2570
Height(guardrail folded)	mm	2030
Platform size	mm	2270x1120
Platform extended	mm	900
Ground clearance (Lower)	mm	100
Ground clearance (Raised)	mm	19
Wheel base	mm	1895
Min. Turning radius (inner wheels)	mm	0
Min. Turning radius (outer wheels)	mm	2200
Lifting motor/Drive motor	V/Kw	24/4.5
Travel speed(Lower)	Km/h	3.5
Travel speed(Raised)	Km/h	0.8
Lifting/Descend speed	sec	60/50
Battery	V/Ah	4x12/30
Charger	V/A	24/25
Grade ability	%	25
Max. working inclination	.	1.5/ 3
Tyre size	mm	Φ381x127
Overall weight	Kg	2980

Standard equipment

Proportional controls
 Self-lock gate on platform
 Extension Platform
 Drivable at full height
 Non marking tyre
 2WD
 Automatic brakes system
 Emergency lowering system
 Emergency stop button
 Tubing explosion-proof system
 Onboard diagnostic system
 Tilt sensor with alarm
 All Motion Alarm
 Horn
 Hour meter
 Safety brackets
 Forklift pockets
 Charger protection
 Flashing beacon
 Folding guardrails
 Automatic pothole protection

Product Description

As the ideal model for flexible operation in narrow space, hydraulic electric slab scissor lifts feature nice appearances, compact structures, stability, reliability, strong power performance and field adaptability, flexible operation, excellent quality and safety. Scissor Lifts cover 8m to 16m work height, hydraulic powered, electric motor drive, which have long run time, and high productivity. The energy-efficient direct electric drive boosts your productivity with industry-leading duty cycles. It is safe and reliable, so it is the optimal product for aerial lifting operation, such as aerial cleaning, repairing, and maintenance.

Self-propelled Scissor Lifts are energy-saving and environmentally-friendly with less noise and no emission. With proportional controls for lift and drive functions, the CFMG slab scissor lift boasts the versatility to work in indoor and outdoor construction, maintenance and installation applications with firm, level surfaces.

Service

1. All the machines will be full tested before shipment
2. The total machine guarantee is 12 months
3. 24 Hours technical support, email, telephone or video online
4. User-friendly english manual for machine using and maintaining
5. Several sets wearing parts will be free for you



More products available:

Tower Cranes

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform

---Most popular model ZLP630, ZLP800: 630KG AND 800KG





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu
District, Jinan City, Shandong Province, China