

300kg 12m Platform Height Hydraulic Scissor Lift Mobile Skyjack Platform

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- 10-20 days • Payment Terms: Western Union, L/C, T/T
- Supply Ability: 80 sets per month



Product Specification

Condition:	100% New
 Application: 	Load Passengers To Aerial Work
• Type:	Hydraulic Drive
• Load:	320kg
 Working Height: 	14m
 Lifting/Descend Speed: 	60/50 Sec
Lifting Motor/Drive Motor:	24/4.5 V/kw
 Battery: 	4x12/300 V/Ah
• Platform Material:	High Strength Steel
 Platform Size: 	2270x1120 Mm
Color:	Orange,blue, Yellow Or Others

China

ISO,CE

container

HYCM, CHUFENG or others

\$10000-14500 per set

CFPT1214self propelled Scissor Lift Platform

Plywood package, LCL or 20'GP, 40'HC



More Images



300kg 12m Platform Height Hydraulic Scissor Lift Mobile Skyjack Platform

General Introduction of this scissor lifts work platform

- 1. Load capacity: 320kg
- 2. Lifting height: 13.8m

3. Applications: aerial installation, maintenance, clean at the construction sites, workshops, warehouse, hotel, airport, wharf,

- gas station and stadium etc. 4. Custom-made according to the requirement
- 5. The worker can control the scissor lift on the platform when raised by handle .
- 6. The worker can also control the lift on the floor by handle control

Specification of this scissor lifts work platform

Parameter	Unit	CFPT1214
Rated Load Capacity	Kg	320
Extended platform load	Kg	113
Max. working height	m	13.8
Max. platform height	m	11.8
Length (L)	mm	2480
Width (W)	mm	1190
Height(guardrail unfolded)	mm	2570
Height(guardrail folded)	mm	2030
Platform size	mm	2270x1120
Platform extended	mm	900
Ground clearance (Lower)	mm	100
Ground clearance (Raised)	mm	19
Wheel base	mm	1895
Min. Turning radius	mm	0
(inner wheels)	·····	Ŭ
Min. Turning radius	mm	2200
(outer wheels)		
Lifting motor/Drive motor	V/Kw	24/4.5
Travel speed(Lower)	Km/h	3.5
Travel speed(Raised)	Km/h	0.8
Lifting/Descend speed	sec	60/50
Battery	V/Ah	4x12/30
Charger	V/A	24/25
Grade ability	%	25
Max. working inclination		1.5/3
Tyre size	mm	Ф381x127
Overall weight	Kg	2980

Standard equipment of this scissor lifts work platform

Proportional controls Self-lock gate on platform Extension Platform Drivable at full height Non marking tyre 2WD Automatic brakes system Emergency lowering system Emergency stop button Tubing explosion-proof system Onboard diagnostic system Tilt sensor with alarm All Motion Alarm Horn Hour meter Safety brackets Forklift pockets Charger protection Flashing beacon Folding guardrails Automatic pothole protection

Product Description

As the ideal model for flexible operation in narrow space, hydraulic electric slab scissor lifts feature nice appearances, compact structures, stability, reliability, strong power performance and field adaptability, flexible operation, excellent quality and safety. Scissor Lifts cover 8m to 16m work height, hydraulic powered, electric motor drive, which have long run time, and high productivity. The energy efficient direct electric drive boosts your productivity with industry leading duty cycles. It is safe and reliable, so it is the optimal product for aerial lifting operation, such as aerial cleaning, repairing, and maintenance.

Self-propelled Scissor Lifts are energy-saving and environmentally-friendly with less noise and no emission. With proportional controls for lift and drive functions, the CFMG slab scissor lift boasts the versatility to work in indoor and outdoor construction, maintenance and installation applications with firm, level surfaces.

Service

- 1. All the machines will be full tested before shipment
- 2. The total machine guarantee is 12 moths
- 3. 24 Hours technical support, email, telephone or video online
- 4. User-friendly english manual for machine using and maintaining
- 5. Sereral sets wearing parts will be free for you



More products available:

- **Tower Cranes**
- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform

---Most popular model ZLP630, ZLP800: 630KG AND 800KG

 Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane
S 0086-18254159408 C emma1109@foxmail.com C hycmtowercrane.com
No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China