

Low Price TC5013 5T Hammer Head Tower Crane For 10 Layer Building Construction

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition:	100% New
 Application: 	Construction Projects And Buildings
• Type:	Hammer Head
• Load:	5T
 Jib Length: 	50m
• Tip Load:	1.3tons
• Power supply:	380V/50Hz Or According To Client's Requirements
 Working Height: 	For 10 Layer Building Construction
Electric Box:	Schneider
Power Supply:	380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need

China

1

LC TT, LC

HYCM TOWER CRANE

CE, ISO, GOST, CU-TR

TC5013 Tower Crane

\$36900-41900 per set

40 sets per month

Naked packing, 3*40'HC + 1*20 containers.

10 days after receiving the deposit or origin



More Images





Low Price TC5013 5T Hammer Head Tower Crane For 10 Layer Building Construction

Short Parameter

1.QTZ63(TC5013) Topkit Tower Crane 2. Type: fixed and external climbing 3. jib length:50m 4. tip load:1.1.3t 5. max.laod: 5t 6.freestanding height:35m

Specification

	QTZ63 (5013) Tower Crane
m)	50
ity (T)	5
	1.3
ght (m)	35
anchorages (m)	150
ension (m)	1.6×1.6×2.5, square tube 135×10mm
sSpeed (m/min)	70/35/7.0, 35/17/3.5
Motor power (kw)	18/18/5
Speed (r/min)	0.7/0.35
Motor power (kw)	2*3.7
Speed (m/min)	38.6/25.2
Motor power (kw)	1.5/2.2
Speed (m/min)	0.4
Motor power (kw)	4
	24.9
	380V/50Hz, 415/50Hz, 220V/60Hz, ect
	ity (T) pht (m) anchorages (m) ension (m) s Speed (m/min) Motor power (kw) Speed (r/min) Motor power (kw) Speed (m/min) Motor power (kw) Speed (m/min)

Advantage

- 1. 15 years of experience in supplying all kinds of tower cranes.
- 2. Export to more than 20 countries with CE/ ISO/ GOST/ CU-TR Certifications.
- 3. Mobile and internal climbing type tower cranes are also offering.
- 4. Rost blasting and rust protection painting with advanced painting process.
- 5. Strict and experience welding line.
- 6. New designed mast, can be also used to Internal Climbing tower cranes.
- 7. Well known brand mechanism system, Schneider Electronic control system.
- 8. Engineers are available to service machinery overseas.
- 9. For long warranty: 12 months from the B/L date.
- besides, some free easy-worn spare parts are provided with the crane.

Description

External climbing tower cranes are a modern form of balance crane that fixed to the ground on a concrete slab (and sometimes attached to the sides of structures), tower cranes often give the best combination of height and lifting capacity and are used in the construction of tall buildings.

The base is then attached to the mast which gives the crane its height. Further the mast is attached to the slewing unit (gear and motor) that allows the crane to rotate.

On top of the slewing unit there are three main parts which are: the long horizontal jib (working arm), shorter counter-jib, and the tower head.

Safety devices:

- 1): Hoist height limit
- 2): Over speed limit
- 3): Over load limit
- 4): Lifting moment limit
- 5): Slewing angle limit
- 6): Emergency stop button
- 7): Obstruction light (tip of jib, tower head)
- 8): Wind lock device.



0086-18254159408



le hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China