# Factory Price TC6013 Top Slewing Crane Tower 6T Max. Load 40M Height

# Basic Information

Place of Origin: ChinaBrand Name: HYCM

• Certification: ISO, CE Customs Union CU-TR EAC

Model Number: TC6013 Tower Crane

• Minimum Order Quantity: 1 set

• Price: \$51700-62000 per set

Packaging Details: Naked packing, 6\*40'HC containers.
 Delivery Time: 20-30 days after receiving the deposit or

origin LC

• Payment Terms: TT, LC

• Supply Ability: 40 sets per month



## **Product Specification**

Condition: 100% New

Application: Buildings And Projects

• Type: Top Slewing

Max Capacity Load: 6tLong Arm: 60mtsHeight: 40m

Mast Main Chord: Square Tube 135\*12mm
Mast section: 1.6\*1.6\*2.5 M (blcok Type)

• Electric Box: Schneider

Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

• Warranty: 12 Months



## More Images



### **Product Description**

#### **Building Fixing Tower Crane 6ton Max Capacity Load Height 40mts Long Arm 60mts**

#### **Shot Parameters**

1.TC6013 Tower Crane

2. Type: fixed and external climbing

3. Working jib length: 60m

4. Tip load: 1.3t 5. Max.laod: 6t

6.Freestanding height:40m

#### Specification

800KN.m
6t
6t
1.3t
150m
60m
40m
400m
3-50m
0.6r/min
40/20 m/min
0.4 m/min
(a=2)80/40/20; (a=4)40/20/4.25
380V/50Hz or others
46.2kw
Schneider
135*12mm/square tube/Q355B
1.6*1.6*2.5m

#### The process features

- 1) Automatic submerged arc welding is adopted in the main section limbs and chord boom. It has high thermal efficiency, high penetration, high production efficiency, while reducing the pores and crack defects, increases the weld strength and the beautiful appearance.
- 2) We adopt carbon dioxide gas welding; it has heat concentrated, a small welding line, high strength and resistance to rust and crack. it can reduce tress and deformation, it has high strength and resistance to rust and crack.
- 3) Shot blasting is used for masts to strength the hardness of steel surface; enhance the paint adhesion and prolonging its life

#### Description

- 1. The Fixed Tower crane base fixed to the ground on a concrete foundation
- 2. The base is then attached to the mast sections which gives the crane its height.
- 3. Further the mast is attached to the slewing unit that allows the crane to slewing.
- 4. The horizontal jib (working arm) is the part of the crane that carries the load.
- 5. The counter-jib carries a counterweight while the jib suspends the load to and from the center of the crane.
- 6. The crane operator usually stay in the cabin at the top of the tower.
- 7. The lifting hook is operated by the operator using electric motors to manipulate wire rope cables through a system of sheaves which lift the building materials

#### **Pictures**





Other Goods: SC Construction Eelvator



#### SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

# ZLP Suspended Platform



**SJY Scissor Lift** 





# Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane







hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China