

500kg 5m Suspended Work Platforms Power Motor Hoister Climbing Work Cradle Facade Lift

Basic Information

Place of Origin: China

Brand Name: AVITT or others

• Certification: ISO,CE

Model Number: ZLP500 Glass Cleaning Gondola

• Minimum Order Quantity: 1 set

• Price: \$2050-2350 per set

• Packaging Details: LCL or 20'GP, 40'HQ Container

• Delivery Time: 7-10 days

Payment Terms: Western Union, L/C, T/T
Supply Ability: 50 sets per month



Product Specification

Condition: 100% New

Application: Buildings And ProjectsType: Suspended Climbing

Max. Load: 500 KgStandard Height: 100 MRated Speed: 9-11 M/min

Power supply: 380V/50Hz Or According To Client's

Requirements

• Motor Power: 2*1.5 Kw

Platform Material: Steel, Hot Galvanized Or Aluminum

• Platform Length: 5 M

• Highlight: 500kg suspended work platforms,

5m suspended work platforms,

power motor electric suspended platform



500KG 5m Platform Power Motor Hoister Climbing Work Cradle Facade Lift

Description

- 1. The ZLP series powered Suspended Gondola / Cradle / Stage is one new type construction machine.
- 2. It is a substitute of traditional scaffold used for exterior construction, decoration, cleaning and maintenance of high rise building, and is also ideal for applications such as the welding of seagoing ship in shipbuilding industry, cleaning of oil-based paint, installation of elevators, big-size tanks and high chimneys, construction of reservoir dams, and inspection, cleaning and repair of bridges.

Specification

Model		ZLP500
Rated load		500Kg
Lifting speed		8-10m/min
Platform Dimension L×W×H(mm)		5000(2+3m)×720 ×1300
Lifting Height		100 m
Cable		100 m
Steel rope		Ф8.3mm
Hoist	Power	1.5KW*2
	Voltage	380V/50HZ
Safety lock	Permission force of impact	30KN
	Locking Cable Angle	3°~8°
Suspensio	Front beam overhang	1.3~.1.5m
n mechanis m Galvanize d	Support adjustable height	1.44~2.14m
Counterweight includes		800KG
20'ft container load qty		10 sets

- 1. Suspended Cage: Steel or Aluminum Alloy (powder coating or hot galvanization)
- 2. Suspension Mechanism: Steel (powder coating or hot galvanization)
- 3. Electric hoists: LTD5
- 4. Safety Lock: LSF30
- 5. Electric control box: Schneider brand
- 6. Steel wire rope: 8.3mm
- 7. Counterweights: Cement or Cast Iron
- 8. Spare parts

Features:

Easy to use

Cost effective solutions Reasonable price

Picture



More products available: Construction Machinery

Tower Cranes

- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.




Working Platforms ZLP





Gantry Crane



Small Jib Crane





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China