



## TC6013 8t Topkit Tower Crane Top Slewing 1.6\*3m Split Type Mast Section In Kyrgyz

Our Product Introduction

for more products please visit us on [hycmtowercrane.com](http://hycmtowercrane.com)

### Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: TC6013 Tower Crane
- Minimum Order Quantity: 1
- Price: \$69000-79000 per set
- Packaging Details: Naked packing, 4\*40'HC containers per set tower crane
- Delivery Time: 20-30 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 20 sets per month




### Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed Out Climbing
- Load: 8t
- Jib: 60m
- Tip. Load: 1.3t
- Mast section: 1.6\*3m (split Type)
- Electric Box Contractor: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- After-sales Service Provided: Engineers Available To Service Machinery Overseas, Field Maintenance And Repair Service
- Highlight: Topkit Tower Crane split mast section, TC6013 Topkit Tower Crane 1.6\*3m, Topkit Tower Crane with warranty



### More Images



## Product Description

### TC6013 8t Topkit Tower Crane Top Slewing 1.6\*3m Split Type Mast Section In Kyrgyz

#### Quick Details

This tower crane is a topkit head tower crane, includes foundation frame, mast sections (tower body), climbing system, slewing units, horizontal lifting jib / boom, counter-jib, tower head, operation cab, three mechanisms, electric system and safety device. The max. Boom length is 60m which consist of every 6meters and minimum length is 30m. This tower crane freestanding height is 50m and max.height is 150m with more mast section and 5sets anchorages. The max. Load capacity is 8t and tip load at the end jib is 1.3t.

#### Specification

Model	QTZ100(6013) Tower Crane	
Working Radius (m)	60	
Max. Load Capacity (T)	8	
Tip Load (T)	1.3	
Free standing height (m)	50	
Max. Height with anchorages (m)	150	
Mast Section dimension (m)	1.6×1.6×3, 180×18mm	
Hoisting Mechanism	Speed (m/min)	0-80 0-40
	Motor power (kw)	30/30
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	0-40
	Motor power (kw)	3.3/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)	46.2	
Power Supply	380V/50Hz, 220V/60Hz or others	

#### Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information,specific model and price of products will be provided quickly after receiving inquiry.

#### Safety devices:

- 1) Hoist height limit
- 2) Over speed limit
- 3) Over load limit
- 4) Lifting moment limit
- 5) Slewing angle limit
- 6) Emergency stop button
- 7) Obstruction light (tip of jib, tower head)
- 8) Wind lock device.

#### Competitive Advantage

1. Focusing on tower crane exporting for 15 years;
2. Manufacturer's representative;
3. Preferential ex-factory price, excellent product quality and good after-sales service are our pursuit;
4. Our tower cranes had exported to more than 20 countries, such as Vietnam, Philippines, Indonesia, India, Sri Lanka, Cambodia, Russia, Kazakhstan, Brazil, Cyprus, Belgium, Madagascar and Algeria etc.

**We are dedicated to provide you professional solutions with Aclass Service!**

#### Pictures



**More products available: Construction Machinery**

**Tower Cranes**

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

□

**SC Construction Man and Material Elevator**

- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

□

**SS Building Material Lift / Hoist**

- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.





SJY Scissor Lift



Gantry Crane



Double Beam Bridge Crane



Single Beam Bridge Crane



Half gantry crane



Double Girder gantry crane

**Our advantage**

1. Choose high-quality materials
2. One-stop customized service
3. Professional after-sales team



Rubber tyred gantry crane



Electric Hoist



Jib Crane



Electric Winch

## Small Jib Crane



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China