



PT6013 Zoomlion Tower Crane Top Head Type 60m Working Jib 8tons Load Capacity

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTP6013 Flattop Tower Crane
- Minimum Order Quantity: 1
- Price: \$78500-92500 per set
- Packaging Details: Naked packing, 6*40'HC containers Per set
PT6013 Topless tower crane
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 30 sets per month



Product Specification

- Application: Buildings And Projects
- Type: Fixing Hydraulic Climbing
- Load: 8tons
- Working Jib: 60m
- Free Height: 50m-60m
- Mast sectionSn: 1.6*3M L46
- Main Chord: 180*18mm Angle Steel
- Color: Yellow Or Others



More Images



Product Description

PT6013 Zoomlion Tower Crane Top Head Type 60m Working Jib 8tons Load Capacity

Short parameters

- 1.QTZ100(PT6013) Flat Top Tower Crane
2. Type: fixed and external climbing
3. jib length: 60m
4. tip load: 1.3t
5. max.laod: 10t
- 6.freestanding height: 45m

Specification

ated Lifting Moment	1000KN.m
Rated Loading Capacity	8t
Max. Lifting Load	8t
Tip Load	1.3t
Max. Lifting Height	150m
Span	60m
Free standing height	45m
Rope length	400m
Working range	3-60m
Slewing speed	0.6r/min
Trolley speed	40/20 m/min
Jacking-up speed	0.4 m/min
Hoisting speed(m/min)	(a=2)0-80 (a=4)0-40 control with inverter
Power supply	380V/50Hz or according to client's requirments
Power Capacity	46.2kw
Electric switch box	Schneider
Main materials	135*12mm / 180*10mm
Mast section dimensions	1.835*1.835*2.5 m or 1.6*1.6*3m or others

Our advantage

1. 15 years of experience in supplying new external climbing tower crane with HYCM Brand.
2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
3. Stationary/Traveling and internal climbing type tower crane are available
4. Impeller blasting/rust protection paint
5. Advanced painting process
6. Strict and experience welding line
7. New designed mast, can be used to Internal and external climbing tower crane
8. Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
9. Engineers available to service machinery overseas.
10. For warranty, it is 12 months from the B/L date. What's more, some free easy worn spare parts are provided together with the crane.

Why choose us

1. A professional tower crane supplier in China with 15 years experience
2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
3. Hydraulic self-climbing mechanism
4. Variable-frequency slewing mechanism
5. Varialbe-speed frequency PLC control System
6. Operation data display screen and Safety monitoring system (Black Box)
7. Various safety devices

Components

Mast: the main supporting tower of the crane. It is made of steel trussed sections that are connected together during installation.

Operating cabin: the operating cabin sits just above the slewing unit. It contains the operating controls.

Jib: the jib, or operating arm, extends horizontally from the crane. A "luffing" jib is able to move up and down; a fixed jib has a rolling trolley that runs along the underside to move goods horizontally.

Hook: the hook (or hooks) is used to connect the material to the crane. It hangs at the end of thick steel cables that run along the jib to the motor.

Weights: Large concrete counterweights are mounted toward the rear of the mast, to compensate for the weight of the goods lifted.

Safety Device

1. 3 obstacle lights
2. Height limiter
3. Slewing limiter
4. Range/ trolley limiter
5. Weight limiter
6. Moment limiter
7. Anemometer
8. Block box(optional)

Photos



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China