Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane hycmtowercrane.com

HYCM Factory 6013 Topkit Tower Crane Hammerhead Type 60m Working Jib EXW Price

Basic Information

Place of Origin: ChinaBrand Name: HYCM

Certification: ISO, CE Customs Union CU-TR EAC

Model Number: TC6013 Tower Crane

• Minimum Order Quantity: 1 set

• Price: \$51700-62000 per set

Packaging Details: Naked packing, 6*40'HC containers per set

TC6013 Tower Crane 40m Height

• Delivery Time: 20-30 days after receiving the deposit or

origin LC

• Payment Terms: TT, LC

Supply Ability: 40 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And Projects

• Type: Top Slewing

Max Capacity Load: 6tLong Arm: 60mtsWorking High: 40 Meter

Mast Main Chord: Square Tube 135*12mm
Mast section: 1.6*1.6*2.5 M (blcok Type)

Electric Box: Schneider

• Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

• Warranty: 12 Months



More Images



Product Description

HYCM Factory 6013 Topkit Tower Crane Hammerhead Type 60m Working Jib EXW Price

Shot Parameters

1.TC6013 Tower Crane

2. Type: fixed and external climbing

3. Working jib length: 60m

4. Tip load: 1.3t 5. Max.laod: 6t

6.Freestanding height:40m

Specification

opecinication	
Rated Lifting Moment	800KN.m
Rated Loading Capacity	6t
Max. Lifting Load	6t
Tip Load	1.3t
Max. Lifting Height	150m
Span	60m
Free standing height	40m
Rope length	400m
Working range	3-50m
Slewing speed	0.6r/min
Trolley speed	40/20 m/min
Jacking-up speed	0.4 m/min
Hoisting speed	(a=2)80/40/20; (a=4)40/20/4.25
Power supply	380V/50Hz or others
Power Capacity	46.2kw
Electric switch box	Schneider
Main materials	135*12mm/square tube/Q355B
Mast section dimensions	1.6*1.6*2.5m

The process features

- 1) Automatic submerged arc welding is adopted in the main section limbs and chord boom. It has high thermal efficiency, high penetration, high production efficiency, while reducing the pores and crack defects, increases the weld strength and the beautiful appearance.
- 2) We adopt carbon dioxide gas welding; it has heat concentrated, a small welding line, high strength and resistance to rust and crack. it can reduce tress and deformation, it has high strength and resistance to rust and crack.
- 3) Shot blasting is used for masts to strength the hardness of steel surface; enhance the paint adhesion and prolonging its life

Description

- 1. The Fixed Tower crane base fixed to the ground on a concrete foundation
- 2. The base is then attached to the mast sections which gives the crane its height.
- 3. Further the mast is attached to the slewing unit that allows the crane to slewing.
- 4. The horizontal jib (working arm) is the part of the crane that carries the load.
- 5. The counter-jib carries a counterweight while the jib suspends the load to and from the center of the crane.
- 6. The crane operator usually stay in the cabin at the top of the tower.
- 7. The lifting hook is operated by the operator using electric motors to manipulate wire rope cables through a system of sheaves which lift the building materials

Pictures





Other Goods: SC Construction Eelvator



SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.

ZLP Suspended Platform



SJY Scissor Lift





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China