

10t Load 3023 Derrik Crane Tower 150m Building Height Internal Tower Crane

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

• Condition: 100% New Inner Tower Crane Dismantle Used • Application: Fixed With Tower Head • Type: • Max.Load: 10tons • Lifting Boom: 30mts 2.3tons • Tip Load: • Power: 380v/50hz, 220V/60HZ Or Others Color: Yellow Or According To Clients Need

China

CE, ISO

1 set

LC

AVITT or others

QD3023 Derrick Crane

\$53900-65900 per set

Western Union, L/C, T/T

10t Derrick Crane

10 sets per month

Naked packing, 1*40'HC containers per set

30 days after receiving the deposit or origin



More Images





Product Description

10t Load 3023 Derrik Crane Tower 150m Building Height Internal Tower Crane

Short Parameters

1.QD100(3023) Derrick Tower Crane 2. Type: fixed 3. jib length: 30m 4. tip load: 2.3t 5. max.laod: 10t 6.height:150m or others according to clients needs

Specification

Derrick Crane Specification
1000KN.m
10t
10t
2.3t
150m
30m
3 to 30m
0-0.6r/min
0-10 m/min
0-80 0-40 m/min
380V/50Hz or others
Schneider
1250.45

Description of Derrick Crane

The derrick crane was conceived as a specialist disassemble crane for stripping down cranes on tall buildings, bridge pylons and telecommunication towers.

The dimensions and weights of all individual parts on the new crane are therefore designed to enable them to be dismantled with the aid of a very small hoist and removed via lift shafts in buildings.

Feature

(1) Reasonable structure for less costing and maintenance.

- (2) Favorable performance to improve your working capacity.
- (3) Smooth starting and stopping to improve you security sense.
- (4) Low noise, commodious cabin and good view can make you happiness operating and accurate operating.
- (5) Credible electric parts to guarantee the crane safety in operating.

Safety device

- (1) Weight overload protection device
- (2) Lifting height limit device
- (3) Voltage lower protection function
- (4) Phase sequence protection function
- (5) Emergency stop function

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

- -----Excellent Package
- We provide standard, strong, protective package for our products to prevent it from outer damage.
- -----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Introduction

- 1. The Derrick cranes is fixed to the roof.
- 2. The base is then attached to the slewing unit that allows the crane to sewing.
- 3. On top of the slewing unit there are two main parts which are: the long jib, shorter counter-jib,
- 4. The long jib is the part of the crane that carries the load.
- 5. The crane operator either sits in a cab at the top of the tower or controls the crane by radio remote control from the ground. 6. The lifting hook is operated by the crane operator using electric motors to manipulate wire rope cables through a system of sheaves.

Why chose US

Good Quality: Gotten certification of ISO

Best price: Best offer with suitable payment terms.

Good Sale Service: Technician provided to assistant installment, ect.(Buyer bear the fee).

Delivery on Time: Report order progress. Make sure Delivery on time.

Warranty: Provide a warranty of 12 months from the bill date.

for more products please visit us on hycmtowercrane.com





