

QTZ160 Tower Crane without Head PT6022 10tons Faucet 60m Freestanding Height

Basic Information

Place of Origin: China

Brand Name: HYCM TOWER CRANECertification: CE, ISO, GOST, CU-TR, EAC

Model Number: QTZ160(PT6022) Topless Tower Crane

Minimum Order Quantity: 1

• Price: \$116000-127500 per set

Packaging Details: Naked packing, 7*40'HC or 6*40'HC
Packaging Details: Naked packing, 7*40'HC or 6*40'HC or 6*40'HC

containers per set QTZ160 Topless Tower

Crane

• Delivery Time: 30 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 10 sets per month



Product Specification

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 10 TJib Length: 60 MTip. Load: 2.2 T

• Power supply: 380V/50Hz Or According To Client's

Requirements

• Mast section: 1.835*1.835*2.5 M Or 2*2*3 M (split Type)

• Main Chord: 125*14mm Or 200*20mm



More Images



Product Description

QTZ160 Tower Crane without Head PT6022 10tons Faucet 60m Freestanding Height

Description

PT6022 Topless Tower Crane was a topless split tower crane, various performance indicators have reached international levels, the split mast sections all achieve impeller blasting, improve the surface hardness of steel, enhance the coating adhension, extend equipment useful life. Mast sections adopt split structure, convenient for transportation and storage, save the long distance freight, the main chord of mast section adopts Q345B materials, adaptability to environment. The mechanism adopt domestic famous factory products, reliable performance, good governing performance and shocklessness.

Our company employs 300 skillful personnel and is equipped with Panasonic professional robotic welding equipment, machining centers, large CNC gantry milling, CNC double-sided milling, CNC plasma cutting machines, computer-aided assembly line, fully automated spraying line and so on. Therefore, we can easily meet your requirements.

Specification

Specification	
Туре	Topless or Flattop no head
Max. Lifting Load (t)	10
Tip Load (t)	2.2
Max. Lifting Height with anchorage (m)	200
Free standing height (m)	45-60
Rope length (m)	400
Span (m)	60
Working range (m)	3 to 60
Slewing speed (r/min)	0-0.6
Trolley peed (m/min)	0-60
Jacking-up speed (m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (KW)	61.5
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2)0-80; (a=4)0-50
Mast section (m)	1.835*1.835*2.5 (125*14mm two angle steel with rib) Or 2×2×3, angle steel 200×20mm

FΔQ

Q1: Will you help with installation and stuff training?

Yes, we will send engineers to you and guide the installation and train your workers.

Q2: How do you control the quality?

We insist the "Quality is priority"always pay attention to quality control from the very the beginning to the end .You can also be reassured by our one-year warranty and ISO certificates

Q3:Where is your factory located ?How can i visit there ?

Our factory is located Zhangqiu city, Shandong province, China.

All our clients- from home and abroad are warmly welcome to visit us!

Advantage of Fixed Tower Crane

- 1. 15 years of experience in supplying new tower cranes.
- 2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
- 3. Mobile and internal climbing type tower cranes are also available.
- 4. Impeller blasting and rust protection painting with advanced painting process.
- 5. Strict and experience welding line
- 6. New designed mast, can be used to Internal and external climbing tower crane
- 7. Well known brand mechanism system, Schneider Electronic control system, Jjiangte or Jiuhe motor
- 8. Engineers available to service machinery overseas.
- 9. For warranty: 12 months from the B/L date.

Photos





More products available: Construction Machinery Tower Cranes

- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.



SJY Scissor Lift



Gantry Crane





0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com