

D120 8tongs Self erectile Luffting Tower Crane Standart Section Mast 3 mts 4522 Model

Basic Information

• Place of Origin: China

Brand Name: HYCM TOWER CRANECertification: CE, ISO, GOST, CU-TR

Model Number: QTD120(4522) Luffing Tower Crane

• Minimum Order Quantity: 1 set

• Price: \$101300-107500 per set

• Packaging Details: Naked packing, 6*40'HC containers per set

D4522 Luffing Tower Crane

• Delivery Time: 30 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

Supply Ability: 10 sets per month



Product Specification

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 8 TJib Length: 45 MTip. Load: 2.2 T


Power supply: 380V/50Hz Or According To Client's

Requirements

Mast section: 1.6*1.6*3 M (split Type)
Main Chord: 180*18 Mm (angle Steel)



More Images



Product Description

D120 8tongs Self erectile Luffting Tower Crane Standart Section Mast 3 mts 4522 Model

Performance parameters

- Max. jib length: 45m;
- Max. lifting capacity 8t;
- · Max. hoisting capacity at jib tip:2.2t;
- Rated lifting moment: 1200 Kn.m;
- · Max. freestanding height: 27m; Max. working height of anchored crane: 160m;

Specification

Specification		
Model		QTD120 (4522) Luffing Tower Crane
Working Radius (m)		45
Max. Load Capacity (T)		8
Tip Load (T)		2.2
Free standing height (m)		37
Max. Height with anchorages (m)		160
Mast Section dimension (m)		1.6×1.6×3, angle steel 180×18mm
Hoisting Mechanism	Speed (m/min)	80/40/8.5 40/20/4.25
	Motor power (kw)	24/24/5.4
Slewing Mechanism	Speed (r/min)	0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	10
	Motor power (kw)	30
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	7.5
Total Power (kw)		34
Power Supply		380V/50Hz or according to clients needs

Advantages

Use in extremely restricted areas

Small slewing radii

Modular design

Pre-installed assemblies

Extreme hook heights

Horizontal load movement

Climbing inside buildings

Safety monitoring during climbing

Commercial Terms

Price: Negotiable

Delivery time: 30 days after receiving 30% advanced payment Trade terms: FOB (qingdao) Or CFR, CIF according to Clients needs
Terms of Payment: T/T or L/C (30% advanced payment, 70% before shipment)

Packing: Standard Exporting Packing

Warranty: At least 12 months

Why choose us

- 1. A professional tower crane supplier in China with 15 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

Photos



More products available: Construction Machinery **Tower Cranes**

- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t. ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.




Working Platforms ZLP



SJY Scissor Lift



Gantry Crane



Small Jib Crane



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China