

# sc200/200 2 cabin hoist 130 meter Height 2000kg per cabin and 60hz Energy Lifting People

# **Basic Information**

• Place of Origin: China

Brand Name: AVITT or others

Certification: CE, ISO

Model Number: SC200/200 Passenger Elevator

• Minimum Order Quantity: 1 set

• Price: \$26500-29600 per set

Packaging Details: Naked packing, 1\*40'HC containers per set

SC200/200 Building Elevator

• Delivery Time: 10 days after receiving the deposit or origin

LC

• Payment Terms: Western Union, L/C, T/T

Supply Ability: 40 sets per month



# **Product Specification**

• Condition: 100% New

Application: Buildings And Projects

• Type: With SRIBS Anti-fall Safety Device

Load: 2000kg Per CageHeight: 110 Meters

• Speed: 33 M/min Or Others

• Power supply: 380V/50Hz Or According To Client's

Requirements

Motor Power: 2\*3\*11 Kw Or Others

Motor Brand: Shuangma, Xingxiang, Sanshang, Juli Or

Other

• Mast Section Size: 650\*650\*1508 Mm



# More Images



# **Product Description**

#### sc200/200 2 cabin hoist 130 meter Height 2000kg per cabin and 60hz Energy Lifting People

#### Description

The Elevator is designed for passenger and materials transport. It offers, efficiency, safety, reduced energy consumption and low operating costs, making it the ideal hoist solution for construction and rental companies. A modern microprocessor hoist control system with stop-next-landing control allows for simple operation and ease of use. while a hoist capacity of 4,000 kg offers increased transport capacity at a low cost. With a larger hoist car, higher speeds and increased lifting heights, the SC200/200 is the perfect hoist solution for high-demand and high-rise construction.de new build construction, refurbishment, chimney, offshore and bridge construction.

#### Specification

Model	SC200/200 - Ordinary
Payload capacity	Up to 2 x 2,000 kg
Speed	33m/min or others
Max. lifting height	150 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2 x 3 x 11 kw or others
Safety device	Mechanical interlocking door system to guarantee the highest safety standards.
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 2 racks	158 kg

#### **Humanistic Design**

- 1. Newly designed height of the cage (2.46m), which can save freight.
- 2. Top of the cage is made of a complete high-grade steel, so the waterproof performance is greatly improved.
- 3. Body of cage is made of mesh steel plate, appearance of which with special spray technology which makes cage more beautiful, can completely against rust and prolong its usage life-span.
- 4. Door frame is made by light weight steel shape which can make cage more stable.
- 5. Special embedded counterweight design. More safe and stable in.
- 6. Improved door handle makes the operation more easily.

#### Other models of SC construction hoist

SC50, SC100, SC200, SC100/100 Single and Double Cage with or without Cab for your choice

# Picture







#### More products available:

#### **Tower Cranes**

- ---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- ---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- ---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

### SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m. **ZLP Suspended Platform** 



**SJY Scissor Lift** 





# Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China