

4 Tons Little Inner Climbing Tower Crane Topkit Type 47m Boom For High Buildings

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition:	100% New
 Application: 	Buildings And Projects
• Type:	Fixed And Internal Climbing
• Max. Load:	4t
 Jib Length: 	47m
• Tip. Load:	0.8t
• Power supply:	380V/50Hz Or According To Client's Requirements
 Mast section: 	1.5*1.5*2.2m
 Highlight: 	4 tons inner climbing tower crane, Topkit inner climbing tower crane, High Buildings self climbing tower crane

China

LC

Avitt or others

CE, ISO, GOST, CU-TR

\$41900-49200 per set

Western Union, L/C, T/T

40 sets per month

QTZ40(4708) Inner Climbing Tower Crane

10 days after receiving the deposit or origin

Naked packing, 4*40'HQ containers.



Our Product Introduction

4tons Little Inner Climbing Tower Crane Topkit Type 47m Boom for High Buildings

Description of QTZ40 Internal Climbing Tower Crane

Internal climbing tower crane adopts hydraulic climbing method, usually installed inside the building elevator. The working radius is fully utilized and so the working range is wide, valid hoisting capacity is strong compared to external climbing tower crane.

The crane climbs with the increase of the building height. The maximum hoisting height is 120m and standard mast height is only 26.4 m, which saves lots of purchasing cost, transportation fees and maintenance expenses.

Specification of QTZ40 Internal Climbing Tower Crane

Model	QTZ40 (4708) Tower Crane
Туре	Internal climbing
Rated Lifting Moment(KN.M)	400
Rated Loading Capacity(T)	4
Max. Lifting Load(T)	4
Tip Load(T)	0.8
Mast section height(M)	26.4
Span(M)	47
Working range(M)	3 to 47
Slewing speed(r/min)	0.7/0.35
Trolley peed(m/min)	38.6/25.2
Jacking-up speed(m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity(KW)	24.9
Electric switch box	Schneider
Hoisting speed(m/min)	(a=2) 65.14/32.57/7.0; (a=4) 32.14/15.6/3.5
Mast section(m)	1.5*1.5*2.2

Advantages of QTZ40 Internal Climbing Tower Crane

1. High Climbing Capacity

2. Best Economic Benefit

3. High Reliability

4. Multiple Usages

5. Convenient Installation and Dismantling

New design Internal Climbing system which is center climbing



More products available: Construction Machinery Tower Cranes

---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.

---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.

---D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.

---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.



ZLP Suspended Platform and SJY Scissor Lift





Small Jib Crane



No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China