

H6013 Dahan Tower Crane for Russia with 60M Jib boom L46 Mast Section

Dahan, Hengsheng, HYCM, Avitt or others

Naked packing, 5*40'HC containers per set

20 days after receiving the deposit or origin

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price: \$75500-99000 per set

1

LC TT, LC

China

TOWER CRANE

H6013 Topless Tower Crane

Topless Tower Crane

30 sets per month

Buildings And Projects

EAC, CE, ISO

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

• Application:

• Type:

- Max. Load:
- Jib Length:
- Tip. Load:
- Power supply:
- Mast section: • Main Chord:
- Fixed Without Tower Head 6 T 60 M 1.3 T 380V/50Hz Or According To Client's Requirements 1.6*1.6*3m (split Type) 180*18mm



More Images



Product Description

H6013 Dahan Tower Crane for Russia with 60M Jib boom L46 Mast Section

Short Parameter

- 1. H6013 Flat Top Tower Crane
- 2. Type: fixed and external climbing
- 3. jib length: 60m
- 4. tip load: 1.3t
- 5. max.laod: 6t

6.freestanding height: 50m

Description

1. This tower cranes are a modern form of balance crane that fixed to the ground on a concrete slab, tower cranes often give the best combination of height and lifting capacity and are used in the construction of tall buildings.

2. The base is then attached to the mast which gives the crane its height. Further the mast is attached to the slewing unit (gear and motor) that allows the crane to rotate.

On top of the slewing unit there are three main parts which are: the long horizontal jib (working arm), shorter counter-jib.

Specification

	H6013 Topless Tower Crane
n)	60
ty (T)	6
	1.3
ht (m)	50
nchorages (m)	150
nsion (m)	1.6*1.6*3, 180×18mm
Speed (m/min)	(a=2)0-80; (a=4)0-40
Motor power (kw)	24/24/5.4
Speed (r/min)	0-0.6
Motor power (kw)	2*3.7
Speed (m/min)	0-40
Motor power (kw)	3.3/2.2
Speed (m/min)	0.4
Motor power (kw)	5.5
	34.8
	ht (m) nchorages (m) nsion (m) Speed (m/min) Motor power (kw) Speed (r/min) Motor power (kw) Speed (m/min) Motor power (kw) Speed (m/min)

Feature

- 1. For even higher performances, cranes offer new possibilities for operation: saving time and space.
- 2. Has reduced dimensions in space due to the slewing part without cathead or jib tie bars
- 3. Smaller overall height, erection operations at a reduced height
- 4. Easier overflying of obstacles on site (cranes, electricity lines, cables,..)
- 5. Jib configuration can be changed in the air during evolution of sites

Why choose us

- 1. A professional tower crane supplier in China with 20 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

Photos

for more products please visit us on hycmtowercrane.com





More products available: Construction Machinery Tower Cranes

---- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t. ---- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.

---- PT Topless/Flat Top Tower Cranes: working jib from 30-80m and max.load ----D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.

---QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

SC Construction Man and Material Elevator

----- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

SS Building Material Lift / Hoist

----- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.



SJY Scissor Lift



Gantry Crane



