

Double Cages SC200/200 Series Curved Inclined Construction Building Hoist 4000KG Capacity

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition: 100% New
Application: Buildings And Projects
Type: Material And Passenger Hoister
Load: 2000kg Per Cage
Height: 50 Meters
Speed: 0-36 M/min Or Others
Power supply: 380V/50Hz Or According To Client's Requirements

China

CE, ISO

LC

AVITT or others

\$26900-36900 per set

Western Union, L/C, T/T

40 sets per month

2*2*13 Kw Or Others Torin Drive Or Other

650*650*1508 Mm

SC200/200 Construction Elevator

SC200/200 Construction elevator

Naked packing, 1*40'HC containers per set

15 days after receiving the deposit or origin

- Motor Power:
- Motor Brand:
- Mast Section Size:



Double Cages SC200/200 Series Curved Inclined Construction Building Hoist 4000KG Capacity

Description

The Elevator is designed for passenger and materials transport.

It offers, efficiency, safety, reduced energy consumption and low operating costs, making it the ideal hoist solution for construction and rental companies.

A modern microprocessor hoist control system with stop-next-landing control allows for simple operation and ease of use. while a hoist capacity of 4,000 kg offers increased transport capacity at a low cost.

With a larger hoist car, higher speeds and increased lifting heights, the SC200/200 is the perfect hoist solution for highdemand and high-rise construction. de new build construction, refurbishment, chimney, offshore and bridge construction.

Specification

Model	SC200/200
Payload capacity	Up to 2 x 2,000 kg
Speed	0-36m/min or others
Max. lifting height	150 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2 x 2 x 13 kw or others
Safety device	Mechanical interlocking door system to guarantee the highest safety standards.
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 2 racks	158 kg

Curved and inclined passenger and material construction hoist has the following features:

1. It adopts floating self-leveling mechanism to make sure the hoist moves keeping level along the curved and inclined line.

- 2. Mast section adopts special treatment, which can be arranged in curved or inclined shape.
- 3. When mast section is vertical, the machine can also be used as a vertical hoist.
- 4. Brand-name electric parts, e.g. SRIBS, Schneider, Siemens, SJJ etc. are applied to ensure the equipment works steadily. 5. It is widely used in such constructions as chimneys, cooling towers and bridges etc.

Humanistic Design

1. Newly designed height of the cage, which can save freight.

- 2. Top of the cage is made of a complete high-grade steel, so the waterproof performance is greatly improved.
- 3. Body of cage is made of mesh steel plate, appearance of which with special spray technology which makes cage more beautiful, can completely against rust and prolong its usage life-span.
- 4. Door frame is made by light weight steel shape which can make cage more stable.
- 5. Special embedded counterweight design. More safe and stable in.
- 6. Improved door handle makes the operation more easily.

Other models of SC construction hoist

SC50, SC100, SC200, SC100/100 Single and Double Cage with or without Cab for your choice

Picture



No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China