

PT3510 2.5T Topless Tower Crane Inner Climbing Type With Inverter Control

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Avitt, Kangtai or others
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ40(3510) Inner Climbing Tower Crane
- Minimum Order Quantity: 1 set
- Price: \$39800-49900 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed And Internal Climbing
- Max. Load: 4t
- Jib Length: 35m
- Tip. Load: 1.0t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.2*1.2*3m S24
- Highlight: Inverter Control Topless Tower Crane,
PT3510 Topless Tower Crane,
Inner Climbing Topless Tower Crane

for more products please visit us on hycmtowercrane.com

Product Description

PT3510 2.5T Topless Tower Crane inner Climbing type with Inverter Control

Description of QTZ40 Internal Climbing Tower Crane

Internal climbing tower crane adopts hydraulic climbing method, usually installed inside the building elevator. The working radius is fully utilized and so the working range is wide, valid hoisting capacity is strong compared to external climbing tower crane.

The crane climbs with the increase of the building height. The maximum hoisting height is 120m and standard mast height is only 26.4 m, which saves lots of purchasing cost, transportation fees and maintenance expenses.


Specification of QTZ40 Internal Climbing Tower Crane

Model	QTZ40 (3510) Tower Crane
Type	Internal climbing
Rated Lifting Moment(KN.M)	400
Rated Loading Capacity(T)	4
Max. Lifting Load(T)	4
Tip Load(T)	1.0
Mast section height(M)	21
Span(M)	35
Working range(M)	3 to 35
Slewing speed(r/min)	0.7/0.35
Trolley speed(m/min)	38.6/25.2
Jacking-up speed(m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity(KW)	24.9
Electric switch box	Schneider
Hoisting speed(m/min)	(a=2) 65.14/32.57/7.0; (a=4) 32.14/15.6/3.5
Mast section(m)	1.2*1.2*3

Advantages of QTZ40 Internal Climbing Tower Crane

1. High Climbing Capacity
2. Best Economic Benefit
3. High Reliability
4. Multiple Usages
5. Convenient Installation and Dismantling

New design Internal Climbing system which is center climbing





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China