## Avitt

# Types of Topkit Tower Cranes QTZ40(4810) 4tons With Tower Head

### **Basic Information**

• Place of Origin: China

Brand Name: AVITT or others

Certification: CE, ISO, GOST, CU-TR

Model Number: QTZ40(4810)

Minimum Order Quantity:

• Price: \$25400-26900 per set

Packaging Details: Naked packing, 3\*40'HQ containers.

• Delivery Time: 10 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 40 sets per month



## **Product Specification**

• Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 4tJib Length: 48mTip. Load: 1.0t

• Power supply: 380V/50Hz Or According To Client's

Requirements

• Mast section: 1.5\*1.5\*2.2m



### **Product Description**

## Types of Topkit Tower Cranes QTZ40(4810) 4tons With Tower Head

#### **Shot introduction**

QTZ4810 Hammerhead tower crane for sale Fixed / stationary /anchored tower crane

Max. load: 4ton Tip load: 1.0ton Jib length: 48m

CE, ISO, GOST, CU-TR certificate

#### Specification

| Rated Lifting Moment (KN.M) | 400   |
|-----------------------------|---|
| Туре                        | Fixed with tower head                           |
| Rated Loading Capacity (t)  | 4   |
| Max. Lifting Load (t)       | 4   |
| Tip Load (t)                | 1.0   |
| Max. Lifting Height (m)     | 120   |
| Free standing height (m)    | 29  |
| Rope length (m)             | 320   |
| Span (m)                    | 48  |
| Working range (m)           | 3 to 48   |
| Slewing speed (r/min)       | 0.7/0.35  |
| Trolley peed (m/min)        | 38.6/25.2                                       |
| Jacking-up speed (m/min)    | 0.4   |
| Counter jib length (m)      | 12.89   |
| Power supply                | 380V/50Hz or according to client's requirements |
| Power Capacity (kw)         | 24.9  |
| Electric switch box         | Schneider                                       |
| Hoisting speed (m/min)      | (a=2) 64.15/32.57/7.0; (a=4) 32.14/15.60/3.5    |
| Mast section (m)            | 1.5*1.5*2.2m (140*12 /angle steel /Q235B)       |

#### Details:

- 1. Advanced technical parameters, max. Radius is 50m, the static height is 30m, it can reach up to max. height 120m by adding mast sections and anchorages.
- 2. Various tower crane types, such as stationary, external climbing and internal climbing types, is widely used in different construction sites.
- 3. Good speed adjusting performance, excellent stability.
- 4. Simple maintenance and reliable work.
- 5. Advanced electronic appliances, such as Schneider.
- 6. Equipped with excellent safety devices produced by world-class technology, including weight limiter, moment limiter, height limiter, radius limiter, slewing limiter, slewing and trolleying brakes.
- 7. Anti-broken wire rope device and anti-broken shaft device









0086-18254159408

emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China