New Design D2520 Small Luffing Tower Crane 3t export to Korea

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM, HENGHENG, AVITT TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: D2520
- Minimum Order Quantity: 1 set
- Price: $88800-94500 per set
- Packaging Details: Naked packing, 6*40'HQ containers.
- Delivery Time: 30 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 10 sets per month

Product Specification

- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 6t
- Jib Length: 25m
- Tip. Load: 2.0t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.6*1.6*3m (split Type)
- Main Chord: 180*18mm (angle Steel)
- Highlight: **small luffing tower crane 3t**, **D2520 luffing tower crane**, **export luffing tower crane Korea**

More Images

for more products please visit us on hycmtowercrane.com

Our Product Introduction

Product Description

New Design D2520 Small Luffing Tower Crane 3t export to Korea

Short Introduction of Luffing Tower Crane

To meet the requirements of your sites which are crowded, where there are numerous cranes, or which are especially lacking in space, luffing tower cranes meet the challenge.

Advantages of Luffing Tower Crane

Use in extremely restricted areas
Small slewing radii
Modular design
Pre-installed assemblies
Extreme hook heights
Horizontal load movement
Climbing inside buildings
Safety monitoring during climbing

Specification

Model		QTD2520 Luffing Tower Crane
Working Radius (m)		25
Max. Load Capacity (T)		6
Tip Load (T)		2.0
Free standing height (m)		27
Max. Height with anchorages (m)		160
Mast Section dimension (m)		1.6×1.6×3, angle steel 180×18mm
Hoisting Mechanism	Speed (m/min)	80/40/8.5 40/20/4.25
	Motor power (kw)	24/24/5.4
Slewing Mechanism	Speed (r/min)	0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	10
	Motor power (kw)	30
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	7.5
Total Power (kw)		34
Power Supply		380V/50Hz or according to clients needs

Our Skilled Team

Our R&D team is made up of the most prestigious, experienced engineers and experts in this field. Our technicians team are all experienced senior mechanicians.
We provide satisfactory service (pre-sale, while-sale, after-sale).
Our professional advice and instruction are always available and acceptable.

Model	Max.load	Jib length	Tip load	Freestanding height	Mast section size
D63(2520)	**3t/6t**	**25m**	**2.0t**	**35m**	**1.2×1.2×3.0m**
D80(3520)	**5t/6t**	**35m**	**2.0t**	**30m**	**1.2×1.2×3.0m**
D80(4015)	**5t/6t**	**40m**	**1.5t**	**30m**	**1.2×1.2×3.0m or L46**
D120(4522)	**6t/8t**	**45m**	**2.2t**	**27m**	**L46 1.6×1.6×3.0m**
D120(5015)	**6t/8t**	**50m**	**1.5t**	**27m**	**L46 1.6×1.6×3.0m**
D125(5020)	**10t**	**50m**	**2.0t**	**37.5m**	**L68 2×2×3.0m**
D160(5030)	**12t**	**50m**	**3.0t**	**37.5m**	**L68 2×2×3.0m**

Spare Parts

for more products please visit us on hycmtowercrane.com

emma1109@foxmail.com
HYCM

emma1109@foxmail.com
HYCM

emma1109@foxmail.com
HYCM

Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086 18254159408 emma1109@foxmail.com hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China